Change every 50 hours

## MANITOU MANISCOPIC MLT MLT 523 MONO-ULTRA SERIES B-E2 PERKINS



1103C-33 (2004-2008)

ENGINE Perkins 1103C-33 Capacity: 6,9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40
Check every 8 hours, change every 12 mg	onths/ 500 hours	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

AXLE OSCILLATION REAR		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Q7 MP Calcep Grease WR 2	Caliplex HD Grease EP 2	Q5 MP Calcep Grease EP 2

Capacity: 4 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
Check every 250 hours, change every 500	) hours/ 12 months	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
Change every 50 hours		

## **MANITOU MANISCOPIC MLT MLT 523 MONO-ULTRA SERIES B-E2 PERKINS**



1103C-33 (2004-2008)

	CLIMATE
	Moderate
) hours/ 12 months	
	CLIMATE
	Moderate
	0 hours/ 12 months

HUB REDUCTIONS FRONT Capacity: 0,9 liter (each hub)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 250 hours, change every 1000 hours/12 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Change every 50 hours		

HUB REDUCTIONS REAR Capacity: 0,9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Check every 250 hours, change eve	ery 1000 hours/ 12 months	•

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Change every 50 hours		

## MANITOU MANISCOPIC MLT MLT 523 MONO-ULTRA SERIES B-E2 PERKINS 1103C-33 (2004-2008)



TRANSFERBOX
Capacity: 0,75 liter

USE

Normal

Moderate

Agrifluid HT

HYDRAULIC SYSTEM
Capacity: 123 liter (Hydraulic tank)

USE

Normal

PRODUCT RECOMMENDATION 1

Perlus H 46

Change every 1000 hours/ 12 months

HYDRAULIC BRAKE SYSTEM

USE CLIMATE

Normal Moderate

PRODUCT RECOMMENDATION 1

LHM +

Check every 50 hours, change every 1000 hours/ 12 months

COOLING SYSTEM
Capacity: 24 liter

USE

Normal

PRODUCT RECOMMENDATION 1

Coolant SP 15+

Coolant SP 12

CLIMATE

Moderate

PRODUCT RECOMMENDATION 2

PRODUCT RECOMMENDATION 3

Coolant -38 Organic NF

SLIDING PADS JIB		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Q7 MP Calcep Grease WR 2	Caliplex HD Grease EP 2	Q5 MP Calcep Grease EP 2

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Change every 2000 hours