PRODUCT RECOMMENDATION

MANITOU MANISCOPIC MT/MTA MT 10055XT JOHN DEERE 4045T TIER 3 (18201-



>)

ENGINE John Deere 4045 T Capacity: 14,7 liter		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra 10W-40	Agrisynth LSP 10W-40	Agridiesel CRD+ 15W-40
Change every 100 hours		
USE		CLIMATE
Normal, fuel sulfur level < 0,1 %		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra 10W-40	Agrisynth LSP 10W-40	Agridiesel CRD+ 15W-40
Check every 10 hours, change every 25	50 hours/ 3 months	

DIFFERENTIAL FRONT Dana Capacity: 14 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT-Plus	

Check every 250 hours, change every 1000 hours/ 12 months

DIFFERENTIAL REAR Dana Capacity: 14 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT-Plus		
Chook overy 250 hours, change every	1000 hours / 12 months	

Check every 250 hours, change every 1000 hours/12 months

HUB REDUCTIONS FRONT Capacity: 1,8 liter (each hub)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT-Plus		
Check every 250 hours, change every 1000 hours/ 12 months		

PRODUCT RECOMMENDATION

MANITOU MANISCOPIC MT/MTA MT 10055XT JOHN DEERE 4045T TIER 3 (18201-



>)

HUB REDUCTIONS REAR Capacity: 1,75 liter (each hub)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT-Plus	
Check every 250 hours, change every 1000 hours/ 12 months	

TRANSMISSION POWERSHIFT Clark T12000 3/3 Capacity: 22,7 liter (+ cooler)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

Check every 10 hours, change every 1000 hours/12 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

Change every 100 hours

HYDRAULIC SYSTEM Capacity: 170 liter (Hydraulic system including tank), Capacity: 113,5 liter (Hydraulic tank)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 46		

Check every 10 hours, change every 2000 hours/24 months

HYDRAULIC BRAKE SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	
Check every 10 hours, change every 1000 hours/ 12 months		

PRODUCT RECOMMENDATION

MANITOU MANISCOPIC MT/MTA MT 10055XT JOHN DEERE 4045T TIER 3 (18201-



>

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM

Capacity: 16,3 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.