

MANITOU MANISCOPIC MT/MTA MT 1335 ST3B PERKINS 854E-E34TA STAGE IIIB (2014 AND AFTER)



ENGINE Perkins 854E-E34TA
Capacity: 7,5 liter

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1

Dieselfleet MSP 15W-40

Change every 50 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Agrisynth LSP Ultra FE 5W-30

PRODUCT RECOMMENDATION 2

Agrisynth LSP Ultra 10W-40

PRODUCT RECOMMENDATION 3

Agrisynth MSP 10W-40

Change every 50 hours

USE	CLIMATE
Normal, fuel sulfur level < 0,001 %	Mediterranean

PRODUCT RECOMMENDATION 1

Dieselfleet MSP 15W-40

Check every 8 hours, change every 500 hours

USE	CLIMATE
Normal, fuel sulfur level < 0,001 %	Moderate

PRODUCT RECOMMENDATION 1

Agrisynth LSP Ultra FE 5W-30

PRODUCT RECOMMENDATION 2

Agrisynth LSP Ultra 10W-40

PRODUCT RECOMMENDATION 3

Agrisynth MSP 10W-40

Check every 8 hours, change every 500 hours

DIFFERENTIAL FRONT Dana
Capacity: 7,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agrifluid HT

Check every 250 hours, change every 500 hours/ 12 months

DIFFERENTIAL REAR Dana
Capacity: 7,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agrifluid HT

Check every 250 hours, change every 500 hours/ 12 months

MANITOU MANISCOPIC MT/MTA MT 1335 ST3B PERKINS 854E-E34TA STAGE IIIB (2014 AND AFTER)

**HUB REDUCTIONS FRONT**

Capacity: 0,75 liter (each)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 250 hours, change every 1000 hours/ 24 months

HUB REDUCTIONS REAR

Capacity: 0,75 liter (each)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 250 hours, change every 1000 hours/ 24 months

TRANSMISSION POWERSHIFT Dana 4/4

Capacity: 21,1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Almirol		

Check every 50 hours, change every 1000 hours/ 24 months

HYDRAULIC SYSTEM

Capacity: 175 liter (Hydraulic tank)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 46		

Check every 50 hours, change every 1000 hours/ 24 months

HYDRAULIC BRAKE SYSTEM

Capacity: 0,75 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
LHM +		

Check every 50 hours, change every 2000 hours/ 24 months

MANITOU MANISCOPIC MT/MTA MT 1335 ST3B PERKINS 854E-E34TA STAGE IIIB (2014 AND AFTER)

**COOLING SYSTEM**

Capacity: 17 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 10 hours, change every 2000 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.