# ACURA (USA / CAN) TL UA4, UA5 TL 3.2 (CAN) (2002-2003)



ENGINE J32A1 Capacity: 4,4 liter, Capacity: 5 liter (Dry fill), Filter capacity: 0,4 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Duranza ECO 5W-20				
Change aver (2000 km/ 6 maniha				

Change every 6000 km/ 6 months

TRANSAXLE AUTOMATIC 5/1 Capacity: 7,2 liter (Dry fill), Capacity: 2,9 liter (Service fill)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
SP Matic 4026				
Change every 48000 km/ 24 months				
USE		CLIMATE		
First change only		Moderate		

PRODUCT RECOMMENDATION 1

#### SP Matic 4026

Change every 96000 km/ 36 months

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Check every 1 months, change every 36 months

## POWER STEERING

Capacity: 0-0 liter (Between min and max.)

We are unable to give a standard recommendation for this component. Please contact our service department.

ACURA (USA / CAN) TL UA4, UA5 TL 3.2 (CAN) (2002-2003)



COOLING SYSTEM Capacity: 7,5 liter (Dry fill), Capacity: 5,6 liter (Service fill)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Coolant SP 14+				
Change every 96000 km/ 60 months				
USE		CLIMATE		
First change only		Moderate		
PRODUCT RECOMMENDATION 1				
Coolant SP 14+				
Change every 192000 km/ 120 months				

### AIRCONDITIONING COMPRESSOR

We are unable to give a standard recommendation for this component. Please contact our service department.

### **AIRCONDITIONING SYSTEM**

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.