# ALFA ROMEO (EU) 159 939 159 2.0 JTDM 16V ECO (125 KW) (2009-2011)



ENGINE 939B3000 Capacity: 4,9 liter		
USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Presteza MSP 5W-30	Avanza MSP+ 5W-30	Avanza RPC 5W-30

Check every 3000 km, change every 30000 km/24 months

TRANSAXLE MANUAL 6/1 Capacity: 2,8 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 5015	

HYDRAULIC BRAKE/CLUTCH SYSTEM ABS		
	CLIMATE	
	Moderate	
PRODUCT RECOMMENDATION 2		
Drauliquid-S DOT 4		
	PRODUCT RECOMMENDATION 2	CLIMATE Moderate PRODUCT RECOMMENDATION 2

Change every 30000 km/ 24 months

POWER STEERING	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Fluid 3013	
Check every 24 months/ 30000 km	

### GREASE POINTS/NIPPLES HOMOKINETIC JOINTS DIFFERENTIAL SIDE

### Capacity: 160 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

GREASE POINTS/NIPPLES HOMOKINETIC JOINTS WHEEL SIDE Capacity: 282 grams		
use Normal		сымате Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

# ALFA ROMEO (EU) 159 939 159 2.0 JTDM 16V ECO (125 KW) (2009-2011)



COOLING SYSTEM Capacity: 6,1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 24 months/ 30000 km

#### AIRCONDITIONING COMPRESSOR Capacity: 130 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.