

# ALFA ROMEO (EU) 164 164 164 2.5 TD (1989-1992)

**ENGINE VM84A**

Capacity: 7,2 liter (Initial fill), Capacity: 6,7 liter (Service fill)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**Bi-Turbo 15W-40**

Check every 500 km, change every 10000 km/ 12 months

**TRANSAXLE MANUAL 5/1**

Capacity: 1,8 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**SP Gear 5015**

## PRODUCT RECOMMENDATION 2

**Gearlube GL-4 80W**

Check every 20000 km, change every 40000 km/ 24 months

**HYDRAULIC BRAKE/CLUTCH SYSTEM**

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4**

## PRODUCT RECOMMENDATION 2

**Drauliquid-S DOT 4**

Check every 500 km, change every 12 months

**POWER STEERING**

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**ATF Dexron II-D**

Check every 500 km

**COOLING SYSTEM**

Capacity: 10 liter (Initial fill), Capacity: 8 liter (Service fill)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**Coolant -38 Organic NF**

Change every 60000 km/ 24 months

# ALFA ROMEO (EU) 164 164 164 2.5 TD (1989-1992)



*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*