

ASTON MARTIN V8 VANTAGE V8 VANTAGE

(2009-2012)

**ENGINE**

Capacity: 10 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Emperol 5W-50	Emperol Racing 10W-60	

Change every 16000 km/ 12 months

TRANSAXLE MANUAL Graziano 6/1

Capacity: 4,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 5015		

Check every 32000 km/ 24 months, change every 64000 km/ 48 months

TRANSAXLE SEMI-AUTOMATIC Graziano SportShift 6/1

Capacity: 4,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 5015		

Check every 32000 km/ 24 months, change every 64000 km/ 48 months

HYDRAULIC ACTUATION GEARBOX/CLUTCH

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

Check every 16000 km/ 12 months

HYDRAULIC BRAKE/CLUTCH SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-S DOT 4		

Check every 16000 km/ 12 months, change every 24 months

ASTON MARTIN V8 VANTAGE V8 VANTAGE

(2009-2012)



POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

Check every 16000 km/ 12 months

COOLING SYSTEM

Capacity: 14 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 16000 km/ 12 months, change every 160000 km/ 60 months

AIRCONDITIONING

Capacity: 750 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.