ACURA (USA / CAN) MDX YD2 MDX 3.7 V6 (2007-2010)



ENGINE J37A1/A2 Capacity: 5 liter (Dry fill), Capacity: 4,3 liter (Service fill), Filter capacity: 0,3 liter		
	CLIMATE	
em)	Moderate	

DIFFERENTIAL REAR Capacity: 2,5-2,8 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4026	

RANSFERBOX		
Capacity: 0,4-0,5 liter		

Gearlube GL-4 80W-90	Gearlube GL-5 80W-90	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Normal		Moderate
USE		CLIMATE

TRANSMISSION AUTOMATIC 5/1 Capacity: 7,9-8,1 liter (Dry fill), Capacity: 2,8 liter (Service fill)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Check every 1 months, change every 36 months

POWER STEERING Capacity: 0-0 liter (Between min and max.)

We are unable to give a standard recommendation for this component. Please contact our service department.

ACURA (USA / CAN) MDX YD2 MDX 3.7 V6 (2007-2010)



COOLING SYSTEM Capacity: 9,2 liter (Dry fill), Capacity: 7,3 liter (Service fill)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.