## ALFA ROMEO (EU) 156 932 156 2.4 JTD (110 KW) (2002-2003)



ENGINE 841C000 Capacity: 5,5 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Emperol 10W-40			
Check every 500 km, change every 20000 km/ 12 months			
USE		CLIMATE	
Normal		Arctic	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Emperol 5W-40	Asyntho 5W-30		
Check every 500 km, change every 20000	) km/ 12 months		

TRANSAXLE MANUAL 5/1 Capacity: 2 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 5015	SP Gear 1071		
Check every 80000 km/ 48 months	·	'	

HYDRAULIC BRAKE/CLUTCH SYSTEM			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		

Check every 500 km, change every 60000 km/24 months

POWER STEERING		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		
Check every 500 km		

PRODUCT RECOMMENDATION

## ALFA ROMEO (EU) 156 932 156 2.4 JTD (110 **KW)** (2002-2003)



COOLING SYSTEM Capacity: 6,8 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -38 Organic NF	
Check every 500 km, change every 60000 km/ 24 mont	ths

Check every 500 km, change every 60000 km/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.