Change every 15000 km/ 12 months

## **AUDI (EU) A3, S3, RS 3 8V A3 1.6 TDI (77 KW)** (2012-2016)



ENGINE CLHA Capacity: 4,7 liter			
USE		CLIMATE	
Extended drain (max)		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30		
Change every 30000 km/24 months			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30		

TRANSAXLE MANUAL 02S 6/1			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 1081	SP Gear 5015		

TRANSAXLE SEMI-AUTOMATIC S TRONIC 0CW 7/1 Capacity: 1,7 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 1081	SP Gear 5015		

USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Fluid 3013	

PRODUCT RECOMMENDATION

## AUDI (EU) A3, S3, RS 3 8V A3 1.6 TDI (77 KW) (2012-2016)



HYDRAULIC BRAKE SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-LV Super DOT 4	
Change every 24 months	

COOLING SYSTEM Capacity: 0-0 liter (Between min and max.)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 12 EVO	
Check every 24 months/ 30000 km	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.