PRODUCT RECOMMENDATION

ATLAS GMBH TRACKED EXCAVATORS 1704LC DEUTZ BF6M-1013 (1995-2005)

ENGINE Deutz BF6M-1013ECP
Capacity: 21 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Dieselfleet CD+ 15W-40	**Multifleet SHPD 15W-40**	
Change every 500 hours		

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Dieselfleet CD+ 15W-40	**Multifleet SHPD 15W-40**	
Change every 50 hours		

HYDRAULIC SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 46		
Change every 3000 hours		

USE		CLIMATE
Acceptable		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 20W-20		
Change every 3000 hours		

USE		CLIMATE
Acceptable		Cold
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
Change every 3000 hours		

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

ATLAS GMBH TRACKED EXCAVATORS 1704LC DEUTZ BF6M-1013 (1995-2005)

COOLING SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	**Coolant -26**	

PLAIN BEARINGS

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

ROLLER BEARINGS

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	**Q5 MP Calcep Grease EP 2**	**MP Lithep Grease EP 2**

SLEWING RING BALL RACES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	**Q5 MP Calcep Grease EP 2**	**MP Lithep Grease EP 2**

SLEWING RING GEAR TEETH

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Compound OGL EP 0/1		

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

ATLAS GMBH TRACKED EXCAVATORS 1704LC DEUTZ BF6M-1013 (1995-2005)

SWING REDUCTION UNIT

USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
Gearlube GL-5 85W-140		

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

TRAVEL REDUCTION UNIT

USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
Gearlube GL-5 85W-140		

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

WHEEL BEARINGS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Labora Grease	**Q5 MP Calcep Grease EP 2**	**MP Lithep Grease EP 2**

WORM GEARBOX

USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
Gearlube GL-5 85W-140		

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

ATLAS GMBH TRACKED EXCAVATORS 1704LC DEUTZ BF6M-1013 (1995-2005)

advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367