

AUSA WHEELED DUMPERS D 300 AMG

KUBOTA V2203-M (2008 AND AFTER)



ENGINE Kubota V2203
Capacity: 9,5 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	Multifleet SHPD 20W-50

Change every 150 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Kroontrak MTH 10W-30	Synfleet SHPD 10W-40

Change every 150 hours

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	Multifleet SHPD 20W-50

Change every 50 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Kroontrak MTH 10W-30	Synfleet SHPD 10W-40

Change every 50 hours

DIFFERENTIAL FRONT Dana
Capacity: 4,1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Check every 40 hours, change every 900 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Change every 50 hours

AUSA WHEELED DUMPERS D 300 AMG

KUBOTA V2203-M (2008 AND AFTER)



DIFFERENTIAL FRONT Newage

Capacity: 6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Agrifluid HT		

Check every 40 hours, change every 12 months/ 900 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1		
Agrifluid HT		

Change every 50 hours

DIFFERENTIAL REAR Dana

Capacity: 4,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 40 hours, change every 900 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 50 hours

DIFFERENTIAL REAR Newage

Capacity: 3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Agrifluid HT		

Check every 40 hours, change every 12 months/ 900 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1		
Agrifluid HT		

Change every 50 hours

AUSA WHEELED DUMPERS D 300 AMG

KUBOTA V2203-M (2008 AND AFTER)



HUB REDUCTIONS Dana

Capacity: 0,35 liter (each hub)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Check every 40 hours, change every 900 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Change every 50 hours*

TRANSFERBOX Dana

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-4 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90*Check every 40 hours, change every 12 months/ 900 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-4 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90*Change every 40 hours*

TRANSFERBOX Newage

Capacity: 0,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90*Check every 40 hours, change every 12 months/ 900 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90*Change every 50 hours*

AUSA WHEELED DUMPERS D 300 AMG

KUBOTA V2203-M (2008 AND AFTER)



TRANSMISSION MANUAL 3/1

Capacity: 2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 40 hours, change every 12 months/ 900 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 50 hours

HYDRAULIC SYSTEM

Capacity: 45 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus Biosynth 46	Perlus H 46	

Check every 40 hours, change every 900 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus Biosynth 46	Perlus H 46	

Change every 50 hours

HYDRAULIC BRAKE SYSTEM

Capacity: 1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
LHM +	Perlus H 32	Perlus AF 32

Check every 40 hours, change every 900 hours

GREASE POINTS/NIPPLES

We are unable to give a standard recommendation for this component. Please contact our service department.

AUSA WHEELED DUMPERS D 300 AMG

KUBOTA V2203-M (2008 AND AFTER)

**COOLING SYSTEM**

Capacity: 7,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 40 hours, change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.