BELL EQUIPMENT ARTICULATED DUMP TRUCKS B-C-D-E SERIES B30L MK II (4X4) 1015 DEUTZ BF6M1015



| ENGINE Deutz BF6M-1015 Capacity: 29 liter | | |
|--|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Agrisynth LSP 10W-40 | Armado Synth 10W-40 | |
| | | |

Change every 500 hours

| DIFFERENTIAL FRONT Bell | | | |
|---|--|---------------|--|
| USE | | CLIMATE | |
| Normal | | Mediterranean | |
| PRODUCT RECOMMENDATION 1 | | | |
| Gear Oil Alcat 50 | | | |
| Check every 1000 hours, change every 2000 hours | | | |
| USE | | CLIMATE | |
| Initial service | | Mediterranean | |
| PRODUCT RECOMMENDATION 1 | | | |
| Gear Oil Alcat 50 | | | |

Change every 100 hours

| DIFFERENTIAL REAR Bell | | |
|---|--|---------------|
| USE | | CLIMATE |
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 50 | | |
| Check every 1000 hours, change every 2000 hours | | |

| USE | | CLIMATE | |
|--------------------------|--|---------------|--|
| Initial service | | Mediterranean | |
| PRODUCT RECOMMENDATION 1 | | | |
| Gear Oil Alcat 50 | | | |
| Change every 100 hours | | | |

BELL EQUIPMENT ARTICULATED DUMP TRUCKS B-C-D-E SERIES B30L MK II (4X4) 1015 DEUTZ BF6M1015



| TRANSMISSION ZF 6WG210 6/3 Capacity: 26 liter (Dry fill), Capacity: 16 liter (Service fill) | | |
|--|--|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| SP Matic 2032 | | |
| Change every 1000 hours | | |
| USE | | CLIMATE |
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| SP Matic 2032 | | |
| | | |

Change every 100 hours

| HYDRAULIC SYSTEM Capacity: 85 liter (Hydraulic tank) | | |
|---|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Perlus H 46 | Perlus H 68 | Perlus AF 46 |
| Change every 4000 hours | · · · | · · · · |
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| SP Matic 2032 | ATF Almirol | Perlus H 32 |

Change every 4000 hours

| GREASE POINTS/NIPPLES | | |
|--------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

| COOLING SYSTEM Capacity: 34 liter | | | |
|--------------------------------------|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Coolant SP 15+ | Coolant SP 12 | | |
| Change every 2000 hours | | | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products.

BELL EQUIPMENT ARTICULATED DUMP TRUCKS B-C-D-E SERIES B30L MK II (4X4) 1015 DEUTZ BF6M1015



Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.