

BELL EQUIPMENT ARTICULATED DUMP TRUCKS B-C-D-E SERIES B45D MK 7 (6X6) MERCEDES-BENZ OM502LA (STAGE 3A)



ENGINE Mercedes-Benz OM502LA
Capacity: 38 liter (Dry fill)

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Agrisynth LSP 10W-40

PRODUCT RECOMMENDATION 2
Armado Synth 10W-40

Change every 500 hours

DIFFERENTIAL FRONT (WET DISC BRAKES) 27A10HA
Capacity: 70 liter (Dry fill), Capacity: 68 liter (Service fill)

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Kroontrak CVT 10W-40

PRODUCT RECOMMENDATION 2
Agrifluid Synth XHP Ultra

PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus

Change every 1000 hours

DIFFERENTIAL MIDDLE (WET DISC BRAKES) 27A10HB
Capacity: 70 liter (Dry fill), Capacity: 68 liter (Service fill)

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Kroontrak CVT 10W-40

PRODUCT RECOMMENDATION 2
Agrifluid Synth XHP Ultra

PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus

Change every 1000 hours

DIFFERENTIAL REAR (WET DISC BRAKES) 27A10HA
Capacity: 68 liter (Dry fill), Capacity: 70 liter (Service fill)

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Kroontrak CVT 10W-40

PRODUCT RECOMMENDATION 2
Agrifluid Synth XHP Ultra

PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus

Change every 1000 hours

FINAL DRIVES
Capacity: 7 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Kroontrak CVT 10W-40

PRODUCT RECOMMENDATION 2
Agrifluid Synth XHP Ultra

PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus

BELL EQUIPMENT ARTICULATED DUMP TRUCKS B-C-D-E SERIES B45D MK 7 (6X6) MERCEDES-BENZ OM502LA (STAGE 3A)

**TRANSFERBOX VGR 17100**

Capacity: 4,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032*Change every 2000 hours***TRANSMISSION Allison 4600R ORS 6/1**

Capacity: 40 liter (Dry fill), Capacity: 34 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032*Change every 2000 hours***HYDRAULIC SYSTEM**

Capacity: 268,5 liter (Dry fill), Capacity: 256 liter (Hydraulic tank)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Perlus H 46

PRODUCT RECOMMENDATION 2

Perlus H 32

PRODUCT RECOMMENDATION 3

Perlus H 68*Change every 3000 hours***GREASE POINTS/NIPPLES**

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gear Grease EP 1

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

Gear Grease EP 0

BELL EQUIPMENT ARTICULATED DUMP TRUCKS B-C-D-E SERIES B45D MK 7 (6X6) MERCEDES-BENZ OM502LA (STAGE 3A)



COOLING SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.