

BELL EQUIPMENT RIGID TRACTORS & HAULERS 1206 DEUTZ F6L 912



ENGINE Deutz F6L-912
Capacity: 13 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

Multifleet SCD 40

Change every 250 hours/ 6 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agridiesel MSP 15W-40

PRODUCT RECOMMENDATION 2

Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 3

Dieselfleet CD+ 15W-40

Change every 250 hours/ 6 months

USE	CLIMATE
Initial service	Tropical

PRODUCT RECOMMENDATION 1

Multifleet SCD 40

Change every 100 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Agridiesel MSP 15W-40

PRODUCT RECOMMENDATION 2

Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 3

Dieselfleet CD+ 15W-40

Change every 100 hours

BELL EQUIPMENT RIGID TRACTORS & HAULERS 1206 DEUTZ F6L 912


DIFFERENTIAL FRONT ZF

Capacity: 10 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 250 hours, change every 500 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 250 hours, change every 500 hours

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Change every 100 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 100 hours

BELL EQUIPMENT RIGID TRACTORS & HAULERS 1206 DEUTZ F6L 912



DIFFERENTIAL REAR

Capacity: 36 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 250 hours, change every 500 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 250 hours, change every 500 hours

USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Change every 100 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 100 hours

BELL EQUIPMENT RIGID TRACTORS & HAULERS 1206 DEUTZ F6L 912



TRANSMISSION Allison AT 545 4/1
Capacity: 18 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 30

Change every 1000 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 10W

PRODUCT RECOMMENDATION 2

ATF Dexron II-D

Change every 1000 hours

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 30

Change every 100 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 10W

PRODUCT RECOMMENDATION 2

ATF Dexron II-D

Change every 100 hours

HYDRAULIC SYSTEM

Capacity: 55 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.