PRODUCT RECOMMENDATION

BELL EQUIPMENT RIGID TRACTORS & HAULERS 1866A JOHN DEERE 6068TF250

ENGINE John Deere 6068 TF250
Capacity: 19 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	**Agrisynth MSP 10W-40**	**Agridiesel MSP 15W-40**
Change every 250 hours/ 6 months		

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	**Agrisynth MSP 10W-40**	**Agridiesel MSP 15W-40**
Change every 100 hours		

DIFFERENTIAL FRONT
Capacity: 10 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube Racing 75W-140	**Unigear LS GL-3/GL-5 85W-140**	
Check every 250 hours, change every 2000 hours		

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Check every 250 hours, change every 2000 hours		

DIFFERENTIAL REAR Bell 13T
Capacity: 36 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube Racing 75W-140	**Unigear LS GL-3/GL-5 85W-140**	
Check every 250 hours, change every 2000 hours		

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Check every 250 hours, change every 2000 hours		

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

BELL EQUIPMENT RIGID TRACTORS & HAULERS 1866A JOHN DEERE 6068TF250

TRANSMISSION Allison MD 3060P 5/1
Capacity: 8 liter (Dry fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2032		

Check every 250 hours, change every 2000 hours

HYDRAULIC SYSTEM
Capacity: 140 liter (Hydraulic system including tank)

We are unable to give a standard recommendation for this component. Please contact our service department.

GREASE POINTS/NIPPLES WHEEL BEARINGS + DRIVE TRAIN

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	**Q5 MP Calcep Grease EP 2**	**MP Lithep Grease EP 2**

COOLING SYSTEM
Capacity: 22 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	**Coolant SP 12**	**Coolant -38 Organic NF**

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367