

# BELL EQUIPMENT TIMBER TRUCKS / FORWARDERS T T12 (6X6 FORWARDER) CUMMINS 4BTA 3.9C



**ENGINE** Cummins 4BTA3.9C  
Capacity: 8,6 liter

| USE                              | CLIMATE  |
|----------------------------------|----------|
| Normal, fuel sulfur level <0,5 % | Tropical |

PRODUCT RECOMMENDATION 1

**Multifleet SCD 40**

*Change every 250 hours/ 6 months*

| USE                              | CLIMATE       |
|----------------------------------|---------------|
| Normal, fuel sulfur level <0,5 % | Mediterranean |

PRODUCT RECOMMENDATION 1

**Dieselfleet CD+ 15W-40**

PRODUCT RECOMMENDATION 2

**Multifleet SHPD 15W-40**

PRODUCT RECOMMENDATION 3

**Multifleet SCD 30**

*Change every 250 hours/ 6 months*

| USE                              | CLIMATE  |
|----------------------------------|----------|
| Normal, fuel sulfur level <0,5 % | Moderate |

PRODUCT RECOMMENDATION 1

**Kroontrak MTH 10W-30**

PRODUCT RECOMMENDATION 2

**Synfleet SHPD 10W-40**

PRODUCT RECOMMENDATION 3

**Multifleet SHPD 10W-40**

*Change every 250 hours/ 6 months*

| USE                              | CLIMATE |
|----------------------------------|---------|
| Normal, fuel sulfur level <0,5 % | Cold    |

PRODUCT RECOMMENDATION 1

**Multifleet SCD 20W-20**

*Change every 250 hours/ 6 months*

| USE                              | CLIMATE |
|----------------------------------|---------|
| Normal, fuel sulfur level <0,5 % | Arctic  |

PRODUCT RECOMMENDATION 1

**Multifleet SCD 10W**

*Change every 250 hours/ 6 months*

## DIFFERENTIAL FRONT Bell

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90**

# BELL EQUIPMENT TIMBER TRUCKS / FORWARDERS T T12 (6X6 FORWARDER) CUMMINS 4BTA 3.9C

**DIFFERENTIAL MIDDLE Bell**

| USE                         |                                    | CLIMATE  |
|-----------------------------|------------------------------------|----------|
| Normal                      |                                    | Moderate |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |          |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |          |

**DIFFERENTIAL REAR Bell**

| USE                         |                                    | CLIMATE  |
|-----------------------------|------------------------------------|----------|
| Normal                      |                                    | Moderate |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |          |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |          |

**FINAL DRIVES**

| USE                         |                                    | CLIMATE  |
|-----------------------------|------------------------------------|----------|
| Normal                      |                                    | Moderate |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |          |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |          |

**TRANSMISSION Clark 18000 12.6FHR 6/3**  
 Capacity: 17,4 liter

| USE                           |                               | CLIMATE       |
|-------------------------------|-------------------------------|---------------|
| Normal                        |                               | Mediterranean |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2      |               |
| <b>Dieselfleet CD+ 15W-40</b> | <b>Multifleet SHPD 15W-40</b> |               |

| USE                         |                             | CLIMATE                       |
|-----------------------------|-----------------------------|-------------------------------|
| Normal                      |                             | Moderate                      |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3      |
| <b>Kroontrak MTH 10W-30</b> | <b>Synfleet SHPD 10W-40</b> | <b>Multifleet SHPD 10W-40</b> |

| USE                          |                          | CLIMATE |
|------------------------------|--------------------------|---------|
| Normal                       |                          | Cold    |
| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2 |         |
| <b>Multifleet SCD 20W-20</b> | <b>HDX 20W-20</b>        |         |

| USE                       |                          | CLIMATE                  |
|---------------------------|--------------------------|--------------------------|
| Normal                    |                          | Arctic                   |
| PRODUCT RECOMMENDATION 1  | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| <b>Multifleet SCD 10W</b> | <b>HDX 10W</b>           | <b>ATF Almirol</b>       |

# BELL EQUIPMENT TIMBER TRUCKS / FORWARDERS T T12 (6X6 FORWARDER) CUMMINS 4BTA 3.9C



## HYDRAULIC SYSTEM

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>Perlus H 46</b>       | <b>Perlus H 68</b>       |          |

## GREASE POINTS/NIPPLES

| USE                      |                                 | CLIMATE                      |
|--------------------------|---------------------------------|------------------------------|
| Normal                   |                                 | Moderate                     |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
| <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

## COOLING SYSTEM

| USE                           |                          | CLIMATE  |
|-------------------------------|--------------------------|----------|
| Normal                        |                          | Moderate |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2 |          |
| <b>Coolant -38 Organic NF</b> | <b>Coolant -26</b>       |          |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.