

BOBCAT EXCAVATORS 425 KUBOTA V1505-M (2006-2011)



ENGINE Kubota V1505-M
Capacity: 5,5 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SHPD 20W-50	Multifleet SCD 40	

Check every 10 hours, change every 250 hours

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		

Check every 10 hours, change every 250 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40

Check every 10 hours, change every 250 hours

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		

Check every 10 hours, change every 250 hours

USE	CLIMATE
Initial service	Tropical

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SHPD 20W-50	Multifleet SCD 40	

Check every 10 hours, change every 50 hours

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		

Check every 10 hours, change every 50 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40

Check every 10 hours, change every 50 hours

BOBCAT EXCAVATORS 425 KUBOTA V1505-M (2006-2011)



USE		CLIMATE
Initial service		Cold
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
<i>Check every 10 hours, change every 50 hours</i>		

TRAVEL REDUCTION UNIT COMBINED WITH HYDRAULIC SYSTEM Capacity: 0,75 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Perlus AF 100		
<i>Check every 250 hours, change every 6 months/ 1000 hours</i>		

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Perlus H 46	Perlus H 68	Perlus AF 46
<i>Check every 250 hours, change every 6 months/ 1000 hours</i>		

USE		CLIMATE
Acceptable		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Kroontrak MTH 10W-30	HDX 10W	
<i>Check every 250 hours, change every 6 months/ 1000 hours</i>		

TRAVEL REDUCTION UNIT SEPARATE LUBRICATION Capacity: 0,75 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
<i>Check every 250 hours, change every 6 months/ 1000 hours</i>		

HYDRAULIC SYSTEM Capacity: 9,1 liter (Hydraulic tank), Capacity: 20,7 liter (System)		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Perlus AF 100		
<i>Check every 10 hours, change every 6 months/ 1000 hours</i>		

BOBCAT EXCAVATORS 425 KUBOTA V1505-M (2006-2011)



USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 Perlus H 46	PRODUCT RECOMMENDATION 2 Perlus H 68	PRODUCT RECOMMENDATION 3 Perlus AF 46
<i>Check every 10 hours, change every 6 months/ 1000 hours</i>		
USE Initial service		CLIMATE Mediterranean
PRODUCT RECOMMENDATION 1 Perlus AF 100		
<i>Check every 10 hours, change every 6 months/ 100 hours</i>		
USE Initial service		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 Perlus H 46	PRODUCT RECOMMENDATION 2 Perlus H 68	PRODUCT RECOMMENDATION 3 Perlus AF 46
<i>Check every 10 hours, change every 6 months/ 100 hours</i>		
USE Alternative (acceptable)		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 Kroontrak MTH 10W-30	PRODUCT RECOMMENDATION 2 HDX 10W	
<i>Check every 10 hours, change every 6 months/ 1000 hours</i>		
USE Initial service (alternative)		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 Kroontrak MTH 10W-30	PRODUCT RECOMMENDATION 2 HDX 10W	
<i>Check every 10 hours, change every 6 months/ 100 hours</i>		
USE Biodegradable oil		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 Perlus Biosynth 46		
<i>Check every 10 hours, change every 6 months/ 1000 hours</i>		
USE Initial service, biodegradable oil		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 Perlus Biosynth 46		
<i>Check every 10 hours, change every 6 months/ 100 hours</i>		

BOBCAT EXCAVATORS 425 KUBOTA V1505-M (2006-2011)



GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 10 hours

COOLING SYSTEM

Capacity: 8,1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 10 hours, change every 6 months/ 1000 hours

SWING DRIVE GEARBOX

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 50 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.