

# BOBCAT SKID STEER LOADERS 763G H

## S/N 512620000 -> (1999-2001)



**ENGINE** Kubota V2203-M  
Capacity: 7,1 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Multifleet SHPD 20W-50</b>	<b>Multifleet SCD 40</b>	

*Check every 10 hours, change every 250 hours*

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 30</b>		

*Check every 10 hours, change every 250 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak MTH 10W-30</b>	<b>Synfleet SHPD 10W-40</b>	<b>Dieselfleet CD+ 15W-40</b>

*Check every 10 hours, change every 250 hours*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 10W</b>		

*Check every 10 hours, change every 250 hours*

### HYDRAULIC SYSTEM HYDROSTATIC DRIVE

Capacity: 13,2 liter (Hydraulic tank), Capacity: 22 liter (System)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Kroontrak MTH 10W-30</b>	<b>Multifleet SHPD 10W-40</b>	

*Check every 50 hours, change every 1000 hours/ 12 months*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1		
<b>Asyntho 5W-30</b>		

*Check every 50 hours, change every 1000 hours/ 12 months*

# BOBCAT SKID STEER LOADERS 763G H

## S/N 512620000 -> (1999-2001)



### GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

### COOLING SYSTEM

Capacity: 12,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant -33 MPG</b>		

Check every 10 hours

### TRAVEL REDUCTION UNIT

Capacity: 30 liter (Hydraulic tank)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Kroontrak MTH 10W-30</b>	<b>Multifleet SHPD 10W-40</b>	

Check every 50 hours, change every 1000 hours/ 12 months

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
<b>Asyntho 5W-30</b>		

Check every 50 hours, change every 1000 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.