

BOBCAT TELESCOPIC HANDLERS T2566

PERKINS 1004.40T (2000-2004)



ENGINE Perkins 1004.40T
Capacity: 6,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	

Check every 10 hours, change every 600 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	

Change every 100 hours

DIFFERENTIAL FRONT
Capacity: 10,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Agrifluid Synth XHP Ultra	Agrifluid HT-Plus

Check every 100 hours, change every 600 hours

DIFFERENTIAL REAR
Capacity: 10 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Agrifluid Synth XHP Ultra	Agrifluid HT-Plus

Check every 100 hours, change every 600 hours

HUB REDUCTIONS FRONT
Capacity: 0,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Agrifluid Synth XHP Ultra	Agrifluid HT-Plus

Check every 100 hours, change every 600 hours

BOBCAT TELESCOPIC HANDLERS T2566

PERKINS 1004.40T (2000-2004)



HUB REDUCTIONS REAR

Capacity: 0,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Agrifluid Synth XHP Ultra	Agrifluid HT-Plus

Check every 100 hours, change every 600 hours

TRANSFERBOX

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Agrifluid Synth XHP Ultra	Agrifluid HT-Plus

HYDRAULIC SYSTEM

Capacity: 70 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus Biosynth 46	Perlus H 46	

Check every 100 hours, change every 600 hours

HYDRAULIC BRAKE SYSTEM

Capacity: 0,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
LHM +		

Check every 100 hours, change every 600 hours

COOLING SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.