PRODUCT RECOMMENDATION

# CASE BACKHOE LOADERS 695 SUPER R (4WS) FPT F4HE9484C (2008-2020)

## ENGINE FPT F4HE9484C
Capacity: 12,8 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---|---|---|
| **Agridiesel MSP 15W-40** | **Agridiesel CRD+ 15W-40** | **Dieselfleet CD+ 15W-40** |

*Check every 10 hours, change every 500 hours/ 6 months*

## DIFFERENTIAL FRONT
Capacity: 10,5 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---|---|---|
| **Agrifluid Synth XHP Ultra** | **Agrifluid HT-Plus** | **Agrifluid HT** |

*Check every 250 hours, change every 1000 hours/ 12 months*

## DIFFERENTIAL REAR
Capacity: 10,5 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---|---|---|
| **Agrifluid Synth XHP Ultra** | **Agrifluid HT-Plus** | **Agrifluid HT** |

*Check every 250 hours, change every 1000 hours/ 12 months*

## HUB REDUCTIONS
Capacity: 1,3 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---|---|---|
| **Agrifluid Synth XHP Ultra** | **Agrifluid HT-Plus** | **Agrifluid HT** |

*Check every 250 hours, change every 1000 hours/ 12 months*

## TRANSMISSION POWERSHIFT 4/2
Capacity: 14 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **SP Matic 2032** | **ATF Almirol** | |

*Check every 250 hours, change every 1000 hours/ 12 months*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# CASE BACKHOE LOADERS 695 SUPER R (4WS) FPT F4HE9484C (2008-2020)

## TRANSMISSION POWERSHUTTLE 4/4
Capacity: 18 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| **Agrifluid Synth XHP Ultra** | **Agrifluid HT-Plus** | **Agrifluid HT** |

*Check every 250 hours, change every 1000 hours/ 12 months*

## HYDRAULIC SYSTEM
Capacity: 118 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| **Agrifluid Synth XHP Ultra** | **Agrifluid HT-Plus** | **Agrifluid HT** |

*Check every 10 hours, change every 1000 hours/ 12 months*

## HYDRAULIC BRAKE SYSTEM
Capacity: 1 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| **LHM +** | | |

*Check every 10 hours, change every 2000 hours/ 24 months*

## GREASE POINTS/NIPPLES

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| **Labora Grease** | **Q5 MP Calcep Grease EP 2** | **MP Lithep Grease EP 2** |

*Change every 50 hours*

## GREASE POINTS/NIPPLES TELESCOPIC BOOM

We are unable to give a standard recommendation for this component. Please contact our service department.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# CASE BACKHOE LOADERS 695 SUPER R (4WS) FPT F4HE9484C (2008-2020)

| COOLING SYSTEM<br>Capacity: 24 liter | | |
|---|---|---|
| USE<br>Normal | | CLIMATE<br>Moderate |
| PRODUCT RECOMMENDATION 1<br>**Coolant SP 15+** | PRODUCT RECOMMENDATION 2<br>**Coolant SP 12** | |
| *Check every 10 hours, change every 2000 hours/ 24 months* | | |

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367