CASE MINI EXCAVATORS CK/CX CK32



| USE | | CLIMATE |
|--|--------------------------|--------------------------|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Multifleet SHPD 20W-50 | | |
| Check every 10 hours, change every | 250 hours | |
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Kroontrak CVT 10W-40 | Synfleet SHPD 10W-40 | Dieselfleet CD+ 15W-40 |
| Check every 10 hours, change every | 250 hours | |
| USE | | CLIMATE |
| Normal | | Cold |
| PRODUCT RECOMMENDATION 1 Kroontrak MTH 10W-30 | | |
| | | |
| Check every 10 hours, change every | v 250 hours | |
| USE | | CLIMATE |
| Initial service PRODUCT RECOMMENDATION 1 | | Mediterranean |
| Multifleet SHPD 20W-50 | | |
| Check every 10 hours, change every | 50 hours | |
| USE | | CLIMATE |
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Kroontrak CVT 10W-40 | Synfleet SHPD 10W-40 | Dieselfleet CD+ 15W-40 |
| Check every 10 hours, change every | 50 hours | |
| USE | | CLIMATE |
| Initial service | | Cold |
| PRODUCT RECOMMENDATION 1 | | |
| Kroontrak MTH 10W-30 | | |
| Check every 10 hours, change every | 50 hours | |
| | | |
| HYDRAULIC SYSTEM | | |
| USE | | CLIMATE |
| Normal | | Moderate |

Perlus H 46

PRODUCT RECOMMENDATION 1

Check every 10 hours, change every 1000 hours

CASE MINI EXCAVATORS CK/CX CK32



| GREASE POINTS/NIPPLES | |
|--------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| MoS2 Grease EP 2 | |
| Change ayeny 10 hours | |

SWING REDUCTION UNIT

USE

Normal

PRODUCT RECOMMENDATION 1

Gearlube GL-5 85W-140

CLIMATE

Moderate

Moderate

Unigear LS GL-3/GL-5 85W-140

Change every 500 hours

| SWING RING GEAR TEETH | | | |
|--------------------------|----------|--|--|
| USE | CLIMATE | | |
| Normal | Moderate | | |
| PRODUCT RECOMMENDATION 1 | | | |
| MoS2 Grease EP 2 | | | |
| Change every 10 hours | | | |

| TRACK ROLLERS + IDLER WHEELS | | |
|------------------------------|----------|--|
| USE | CLIMATE | |
| Normal | Moderate | |
| PRODUCT RECOMMENDATION 1 | | |
| MoS2 Grease EP 2 | | |
| Change every 10 hours | ' | |

| TRAVEL REDUCTION UNIT | | | | |
|--------------------------|------------------------------|----------|--|--|
| USE | | CLIMATE | | |
| Normal | | Moderate | | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | | |
| Gearlube GL-5 85W-140 | Unigear LS GL-3/GL-5 85W-140 | | | |
| Change every 500 hours | 1 | | | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.