## CASE SKID STEER LOADERS 40XT (2001-2005)



<b>ENGINE</b> Case 4-390 Capacity: 10,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Check every 10 hours, change every 250 hours

HYDRAULIC SYSTEM Capacity: 32,4 liter (Hydraulic tank), Capacity: 1,4 liter (special additive), Capacity: 50,2 liter (Total)				
USE	CLIMATE			
Normal	Moderate			
PRODUCT RECOMMENDATION 1				
Kroontrak MTH 10W-30				
Check eveny 10 hours, change eveny 1000	bours			

Check every 10 hours, change every 1000 hours

GREASE POINTS/NIPPLES				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
MoS2 Grease EP 2				
<u> </u>				

Change every 10 hours

COOLING SYSTEM Capacity: 16,6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 10 hours, change every 2000 hours

DRIVE CHAIN COMPARTMENTS Capacity: 5,7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Multifleet SHPD 10W-40
Change every 1000 hours		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the CASE SKID STEER LOADERS 40XT (2001-2005)



information contained herein is subject to changes without notification.