

CASE TRACKED EXCAVATORS CX

CX225SR ISUZU BB-6BG1T (2002-2008)



ENGINE Isuzu BB-6BG1T
Capacity: 24 liter (Crankcase)

USE
Normal

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1
Multifleet SHPD 20W-50

Check every 10 hours, change every 500 hours

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 2
Dieselfleet CD+ 15W-40

PRODUCT RECOMMENDATION 3
Multifleet SHPD 15W-40

Check every 10 hours, change every 500 hours

USE
Normal

CLIMATE
Cold

PRODUCT RECOMMENDATION 1
Kroontrak MTH 10W-30

PRODUCT RECOMMENDATION 2
Synfleet SHPD 10W-40

PRODUCT RECOMMENDATION 3
Multifleet SHPD 10W-40

Check every 10 hours, change every 500 hours

HYDRAULIC SYSTEM

Capacity: 205 liter (Circuit), Capacity: 120 liter (Oil tank)

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Perlus H 46

PRODUCT RECOMMENDATION 2
Perlus H 22

Check every 10 hours, change every 250 hours

GREASE POINTS/NIPPLES

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
MoS2 Grease EP 2

Change every 10 hours

CASE TRACKED EXCAVATORS CX

CX225SR ISUZU BB-6BG1T (2002-2008)

**COOLING SYSTEM**

Capacity: 23 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 10 hours, change every 1000 hours/ 24 months

SWING REDUCTION UNIT

Capacity: 4,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 250 hours, change every 1000 hours

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 250 hours

TRAVEL REDUCTION UNIT

Capacity: 4,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 250 hours, change every 1000 hours

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 250 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.