PRODUCT RECOMMENDATION

# CATERPILLAR COMPACT TRACKED LOADERS 289D A9Z/TAW/WCT/CATERPILLAR C3.3B DIT

**ENGINE** C3.3B D.T Tier 4i
Capacity: 11,2 liter

| USE | | CLIMATE |
|---|---|---|
| Preferred, fuel sulfur level <0,05% | | Mediterranean |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | |
| **Agridiesel MSP 15W-40** | **Dieselfleet MSP 15W-40** | |

*Check every 10 hours, change every 500 hours/ 12 months*

| USE | | CLIMATE |
|---|---|---|
| Preferred, fuel sulfur level <0,05% | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | |
| **Dieselfleet LSP Ultra 10W-30** | **Dieselfleet MSP 10W-30** | |

*Check every 10 hours, change every 500 hours/ 12 months*

| USE | | CLIMATE |
|---|---|---|
| Fuel sulfur level 0,5-1 % | | Mediterranean |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | |
| **Agridiesel MSP 15W-40** | **Dieselfleet MSP 15W-40** | |

*Check every 10 hours, change every 6 months/ 250 hours*

| USE | | CLIMATE |
|---|---|---|
| Fuel sulfur level 0,5-1 % | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | **PRODUCT RECOMMENDATION 3** |
| **Agrisynth LSP Ultra FE 5W-30** | **Agrisynth LSP Ultra 10W-40** | **Agrisynth MSP 10W-40** |

*Check every 10 hours, change every 6 months/ 250 hours*

| USE | | CLIMATE |
|---|---|---|
| Alternative, fuel sulfur level <0,05% | | Mediterranean |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | |
| **Agridiesel MSP 15W-40** | **Dieselfleet MSP 15W-40** | |

*Check every 10 hours, change every 500 hours/ 12 months*

| USE | | CLIMATE |
|---|---|---|
| Alternative, fuel sulfur level <0,05% | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | |
| **Dieselfleet LSP Ultra 10W-30** | **Dieselfleet MSP 10W-30** | |

*Check every 10 hours, change every 500 hours/ 12 months*

| USE | | CLIMATE |
|---|---|---|
| Fuel sulfur level 0,05-0,5 % | | Mediterranean |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | |
| **Agridiesel MSP 15W-40** | **Dieselfleet MSP 15W-40** | |

*Check every 10 hours, change every 500 hours/ 12 months*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# CATERPILLAR COMPACT TRACKED LOADERS 289D A9Z/TAW/WCT/CATERPILLAR C3.3B DIT (2012 AND AFTER)

| USE | | CLIMATE |
|---|---|---|
| Fuel sulfur level 0,05-0,5 % | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | **PRODUCT RECOMMENDATION 3** |
| **Agrisynth LSP Ultra FE 5W-30** | **Agrisynth LSP Ultra 10W-40** | **Agrisynth MSP 10W-40** |

*Check every 10 hours, change every 500 hours/ 12 months*

## HYDRAULIC SYSTEM

Capacity: 52 liter (Hydraulic system including tank), Capacity: 39 liter (Hydraulic tank)

| USE | | CLIMATE |
|---|---|---|
| Normal | | Mediterranean |
| **PRODUCT RECOMMENDATION 1** | | |
| **Gear Oil Alcat 30** | | |

*Check every 10 hours, change every 2000 hours*

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | **PRODUCT RECOMMENDATION 3** |
| **Agridiesel CRD+ 15W-40** | **Agrifluid HT-Plus** | **Kroontrak MTH 10W-30** |

*Check every 10 hours, change every 2000 hours*

| USE | | CLIMATE |
|---|---|---|
| Biodegradable oil | | Moderate |
| **PRODUCT RECOMMENDATION 1** | | |
| **Perlus Biosynth 46** | | |

*Check every 10 hours, change every 2000 hours*

## GREASE POINTS/NIPPLES

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | | |
| **MoS2 Grease EP 2** | | |

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# CATERPILLAR COMPACT TRACKED LOADERS 289D A9Z/TAW/WCT/CATERPILLAR C3.3B DIT

## COOLING SYSTEM
Capacity: 14 liter

| USE | CLIMATE |
|---|---|
| Preferred, extended | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|---|---|---|
| **Coolant SP 17** | | |

*Check every 10 hours, change every 72 months/ 12000 hours*

| USE | CLIMATE |
|---|---|
| Alternative (acceptable) | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---|---|---|
| **Coolant SP 15+** | **Coolant SP 12** | **Coolant -38 Organic NF** |

*Check every 10 hours, change every 36 months/ 3000 hours*

## TRACK IDLERS
Capacity: 0,35 liter (dual flange), Capacity: 0,35 liter (single flange), Capacity: 0,23 liter (triple flange)

| USE | CLIMATE |
|---|---|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **Agrisynth MSP 10W-40** | **Dieselfleet MSP 15W-40** | |

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---|---|---|
| **Agrisynth LSP Ultra FE 5W-30** | **Agridiesel MSP 15W-40** | **Dieselfleet LSP Ultra 10W-30** |

## TRACK ROLLERS
Capacity: 0,24 liter (each)

| USE | CLIMATE |
|---|---|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **Agrisynth MSP 10W-40** | **Dieselfleet MSP 15W-40** | |

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---|---|---|
| **Agrisynth LSP Ultra FE 5W-30** | **Agridiesel MSP 15W-40** | **Dieselfleet LSP Ultra 10W-30** |

## TRAVEL REDUCTION UNIT
Capacity: 1 liter (each)

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# CATERPILLAR COMPACT TRACKED LOADERS 289D A9Z/TAW/WCT/CATERPILLAR C3.3B DIT (2012 AND AFTER)

| USE | CLIMATE |
|---|---|
| Preferred | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|---|---|---|
| **Gearlube Racing 75W-140** | | |

*Check every 250 hours, change every 500 hours*

| USE | CLIMATE |
|---|---|
| Initial service | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|---|---|---|
| **Gearlube Racing 75W-140** | | |

*Change every 250 hours/ 6 months*

| USE | CLIMATE |
|---|---|
| Alternative (acceptable) | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **Gearlube GL-5 85W-140** | **Unigear LS GL-3/GL-5 85W-140** | |

*Check every 250 hours, change every 500 hours*

| USE | CLIMATE |
|---|---|
| Alternative (acceptable) | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **Gearlube GL-5 80W-90** | **Unigear HS GL-3/GL-5 80W-90** | |

*Check every 250 hours, change every 500 hours*

| USE | CLIMATE |
|---|---|
| Initial service (alternative) | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **Gearlube GL-5 85W-140** | **Unigear LS GL-3/GL-5 85W-140** | |

*Change every 250 hours/ 6 months*

| USE | CLIMATE |
|---|---|
| Initial service (alternative) | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **Gearlube GL-5 80W-90** | **Unigear HS GL-3/GL-5 80W-90** | |

*Change every 250 hours/ 6 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367