PRODUCT RECOMMENDATION

CATERPILLAR FELLER BUNCHERS 541 SERIES 2 F7D (2012 AND AFTER)

ENGINE C9 Acert
Capacity: 39 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agridiesel CRD+ 15W-40	**Multifleet SHPD 15W-40**	

Check every 10 hours, change every 1 months/ 250 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP 10W-40	**Synfleet SHPD 10W-40**	**Dieselfleet CD+ 15W-40**

Check every 10 hours, change every 1 months/ 250 hours

HYDRAULIC HOOD TILT SYSTEM
Capacity: 3,8 liter (Hydraulic tank)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 30	**Gear Oil Alcat 30**	

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	**Agrifluid HT-Plus**	**Kroontrak MTH 10W-30**

HYDRAULIC SYSTEM
Capacity: 318 liter (Hydraulic tank)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 30	**Gear Oil Alcat 30**	

Check every 10 hours, change every 6 months/ 1000 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	**Agrifluid HT-Plus**	**Kroontrak MTH 10W-30**

Check every 10 hours, change every 6 months/ 1000 hours

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

CATERPILLAR FELLER BUNCHERS 541 SERIES 2 F7D (2012 AND AFTER)

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
HT Q9 High Grade Grease	**Labora Grease**	**MoS2 Grease EP 2**

COOLING SYSTEM
Capacity: 36 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 17		

Change every 12000 hours/ 72 months

HUB VARIABLE FAN
Capacity: 0,65-1,22 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

SWING GEAR
Capacity: 21,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
HT Q9 High Grade Grease	**Labora Grease**	**MoS2 Grease EP 2**

Check every 1 months/ 250 hours

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

CATERPILLAR FELLER BUNCHERS 541 SERIES 2 F7D (2012 AND AFTER)

SWING REDUCTION UNIT
Capacity: 10 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Gear Oil Alcat 30	**Gear Oil Alcat 50**	
Check every 10 hours, change every 6 months/ 1000 hours		

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 10 hours, change every 6 months/ 1000 hours		

USE		CLIMATE
Fluid analysis		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Gear Oil Alcat 30	**Gear Oil Alcat 50**	
Check every 250 hours		

USE		CLIMATE
Fluid analysis		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 250 hours		

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

CATERPILLAR FELLER BUNCHERS 541 SERIES 2 F7D (2012 AND AFTER)

TRAVEL REDUCTION UNIT Capacity: 6 liter (each)		
USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 **Gear Oil Alcat 30**	PRODUCT RECOMMENDATION 2 **Gear Oil Alcat 50**	
Check every 10 hours, change every 2000 hours/ 12 months		
USE Normal		CLIMATE Arctic
PRODUCT RECOMMENDATION 1 **Gear Oil Alcat 10W**		
Check every 10 hours, change every 2000 hours/ 12 months		
USE Fluid analysis		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 **Gear Oil Alcat 30**	PRODUCT RECOMMENDATION 2 **Gear Oil Alcat 50**	
Check every 500 hours		
USE Fluid analysis		CLIMATE Arctic
PRODUCT RECOMMENDATION 1 **Gear Oil Alcat 10W**		
Check every 500 hours		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367