

| ENGINE 3406B ATAAC<br>Capacity: 65 liter |                          |               |
|--|--------------------------|---------------|
| USE                                      |                          | CLIMATE       |
| Normal                                   |                          | Mediterranean |
| PRODUCT RECOMMENDATION 1                 | PRODUCT RECOMMENDATION 2 |               |
| Agridiesel CRD+ 15W-40                   | Multifleet SHPD 15W-40   |               |
| Check every 10 hours, change every 1 mo  | onths/ 250 hours         |               |
| USE                                      |                          | CLIMATE       |
| Normal                                   |                          | Moderate      |

| Synfleet SHPD 10W-40     | Dieselfleet CD+ 15W-40   | Multifleet SHPD 10W-40   |
|--------------------------|--------------------------|--------------------------|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |

Check every 10 hours, change every 1 months/250 hours

| HYDRAULIC SYSTEM<br>Capacity: 780 liter (Hydraulic tank), Capacity: 995 liter (System) |                          |               |
|--|--------------------------|---------------|
| USE  |                          | CLIMATE       |
| Normal   |                          | Mediterranean |
| PRODUCT RECOMMENDATION 1   | PRODUCT RECOMMENDATION 2 |               |
| Multifleet SCD 30  | Gear Oil Alcat 30        |               |
| Check every 10 hours, change eve   | ry 2000 hours/ 12 months |               |
| USE  |                          | CLIMATE       |
| Normal   |                          | Moderate      |

| Agridiesel CRD+ 15W-40   | Kroontrak MTH 10W-30     | Synfleet SHPD 10W-40     |
|--------------------------|--------------------------|--------------------------|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| n torritar               |                          | moderate                 |

Check every 10 hours, change every 2000 hours/ 12 months

| GREASE POINTS/NIPPLES    |          |
|--------------------------|----------|
| USE                      | CLIMATE  |
| Normal                   | Moderate |
| PRODUCT RECOMMENDATION 1 |          |
| MoS2 Grease EP 2         |          |



| COOLING SYSTEM<br>Capacity: 95 liter, Capacity: 4,5 liter (Reservoir) |  |          |
|---|--|----------|
| USE   |  | CLIMATE  |
| Normal  |  | Moderate |
| PRODUCT RECOMMENDATION 1  |  |          |
| Coolant SP 17   |  |          |
|   |  |          |

Check every 10 hours, change every 24 months/ 3000 hours

| IDLERS                   |               |
|--------------------------|---------------|
| USE                      | CLIMATE       |
| Normal                   | Mediterranean |
| PRODUCT RECOMMENDATION 1 |               |
| Gear Oil Alcat 50        |               |
|                          |               |
| USE                      | CLIMATE       |
| Normal                   | <br>Moderate  |
| PRODUCT RECOMMENDATION 1 |               |
| Gear Oil Alcat 30        |               |
|                          |               |
| USE                      | CLIMATE       |
| Normal                   | Arctic        |
| PRODUCT RECOMMENDATION 1 |               |
| Gear Oil Alcat 10W       |               |

| SWING REDUCTION UNIT<br>Capacity: 13,5 liter (each) |          |  |
|---|----------|--|
| USE   | CLIMATE  |  |
| Normal  | Moderate |  |
| PRODUCT RECOMMENDATION 1                            |          |  |
| Gear Oil Alcat 50                                   |          |  |

Check every 1 months/ 250 hours, change every 6 months/ 1000 hours

| USE                      | CLIMATE  |
|--------------------------|----------|
| Initial service          | Moderate |
| PRODUCT RECOMMENDATION 1 |          |
| Gear Oil Alcat 50        |          |
| Change every 250 hours   |          |



| TRACK ROLLERS            |               |
|--------------------------|---------------|
| USE                      | CLIMATE       |
| Normal                   | Mediterranean |
| PRODUCT RECOMMENDATION 1 |               |
| Gear Oil Alcat 50        |               |
|                          |               |
| USE                      | CLIMATE       |
| Normal                   | Moderate      |
| PRODUCT RECOMMENDATION 1 |               |
| Gear Oil Alcat 30        |               |
|                          |               |
| USE                      | CLIMATE       |
| Normal                   | Arctic        |
| PRODUCT RECOMMENDATION 1 |               |
| Gear Oil Alcat 10W       |               |

| TRAVEL REDUCTION UNIT<br>Capacity: 25 liter (each) |                             |               |
|--|-----------------------------|---------------|
| USE  |                             | CLIMATE       |
| Normal   |                             | Mediterranean |
| PRODUCT RECOMMENDATION 1                           |                             |               |
| Gear Oil Alcat 50                                  |                             |               |
| Check every 1 months/ 250 hours, change            | every 12 months/ 2000 hours |               |
| USE  |                             | CLIMATE       |
| Normal   |                             | Moderate      |
| PRODUCT RECOMMENDATION 1                           |                             |               |
| Gear Oil Alcat 30                                  |                             |               |
| Check every 1 months/ 250 hours, change            | every 12 months/ 2000 hours |               |
| USE  |                             | CLIMATE       |
| Normal   |                             | Arctic        |
| PRODUCT RECOMMENDATION 1                           |                             |               |
| Gear Oil Alcat 10W                                 |                             |               |
| Check every 1 months/ 250 hours, change            | every 12 months/ 2000 hours |               |
| USE  |                             | CLIMATE       |
| Initial service                                    |                             | Mediterranean |
| PRODUCT RECOMMENDATION 1                           |                             |               |
| Gear Oil Alcat 50                                  |                             |               |
| Change every 250 hours                             |                             |               |
|  |                             |               |



| USE                      | CLIMATE  |
|--------------------------|----------|
| Initial service          | Moderate |
| PRODUCT RECOMMENDATION 1 |          |
| Gear Oil Alcat 30        |          |
| Change every 250 hours   |          |
| USE                      | CLIMATE  |
| Initial service          | Arctic   |
| PRODUCT RECOMMENDATION 1 |          |
| Gear Oil Alcat 10W       |          |
|                          |          |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.