Check every 10 hours, change every 1 months/ 250 hours

CATERPILLAR MOTOR GRADERS 143H 1AL

(1995-2005)



ENGINE 3306 Capacity: 29 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40
Check every 10 hours, change every 1 mg	onths/ 250 hours	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrisynth LSP 10W-40	Multifleet SHPD 10W-40	

TANDEM DRIVE Capacity: 80 liter (each side)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
Check every 1 months/ 250 hours, change every 12 months/ 2000 hours		
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 1 months/ 250 hours, change every 12 months/ 2000 hours		

TRANSAXLE Capacity: 47 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
Check every 1 months/ 250 hours, change	e every 6 months/ 1000 hours	
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 1 months/ 250 hours, change	every 6 months/ 1000 hours	

CATERPILLAR MOTOR GRADERS 143H 1AL

(1995-2005)



Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Normal		Moderate
USE		CLIMATE
Check every 50 hours, change every 4000 hours		
Gear Oil Alcat 30		
PRODUCT RECOMMENDATION 1		
Normal		Mediterranean
USE		CLIMATE
HYDRAULIC SYSTEM Capacity: 38 liter (Hydraulic tank)		

WHEEL SPINDLE BEARING FRONT Capacity: 0,5 liter (each wheel)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
Check every 1 months/ 250 hours		
USE		CLIMATE
Normal		Arctic

USE	CLIMATE
Normal	Arctic
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 10W	
	·

Check every 1 months/ 250 hours

Check every 50 hours, change every 4000 hours

COOLING SYSTEM Capacity: 45 liter			
USE		CLIMATE	
Preferred, extended		Moderate	
PRODUCT RECOMMENDATION 1			
Coolant SP 17			
Check every 10 hours, change every	72 months/ 6000 hours	'	

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
Check every 10 hours, change eve	ery 24 months/ 3000 hours	

Check every 10 hours, change every 24 months/ 3000 hours

CATERPILLAR MOTOR GRADERS 143H 1AL

(1995-2005)



CIRCLE DRIVE GEARBOX Capacity: 7 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 10 hours, change every 2000 hours/ 12 months

use Normal		climate Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube Racing 75W-140	SP Gear 1011	Syngear TDL 75W-90

Check every 10 hours, change every 2000 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.