## CATERPILLAR TRACKED EXCAVATORS 235 83X (1973-1986)



ENGINE Capacity: 27 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		
Change every 250 hours/ 1 months		
JSE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40
Change every 250 hours/ 1 months		
JSE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
Change every 250 hours/ 1 months	'	'
Capacity: 53 liter (each side)		CLIMATE
Capacity: 53 liter (each side)		climate Moderate
Capacity: 53 liter (each side) use Normal		
Capacity: 53 liter (each side)  USE  Normal  PRODUCT RECOMMENDATION 1		
Capacity: 53 liter (each side)  USE  Normal  PRODUCT RECOMMENDATION 1		
Capacity: 53 liter (each side)  USE  Normal  PRODUCT RECOMMENDATION 1  Multifleet SCD 30		
Capacity: 53 liter (each side)  USE  Normal  PRODUCT RECOMMENDATION 1  Multifleet SCD 30  HYDRAULIC SYSTEM		
Capacity: 53 liter (each side)  USE  Normal  PRODUCT RECOMMENDATION 1  Multifleet SCD 30  HYDRAULIC SYSTEM  Capacity: 329 liter		
Capacity: 53 liter (each side)  USE  Normal  PRODUCT RECOMMENDATION 1  Multifleet SCD 30  HYDRAULIC SYSTEM  Capacity: 329 liter  USE		Moderate
Capacity: 53 liter (each side)  USE  Normal  PRODUCT RECOMMENDATION 1  Multifleet SCD 30  HYDRAULIC SYSTEM  Capacity: 329 liter  USE  Normal		Moderate
Capacity: 53 liter (each side)  USE  Normal  PRODUCT RECOMMENDATION 1  Multifleet SCD 30  HYDRAULIC SYSTEM  Capacity: 329 liter  USE  Normal  PRODUCT RECOMMENDATION 1		Moderate
Capacity: 53 liter (each side)  USE  NORMAL  PRODUCT RECOMMENDATION 1  Multifleet SCD 30  HYDRAULIC SYSTEM  Capacity: 329 liter  USE  NORMAL  PRODUCT RECOMMENDATION 1  Gear Oil Alcat 30	nge every 12 months/ 2000 hours	Moderate
FINAL DRIVES Capacity: 53 liter (each side)  use Normal  PRODUCT RECOMMENDATION 1  Multifleet SCD 30  HYDRAULIC SYSTEM Capacity: 329 liter  use Normal  PRODUCT RECOMMENDATION 1  Gear Oil Alcat 30  Check every 3 months/ 500 hours, charuse  Use Normal	nge every 12 months/ 2000 hours	Moderate
Capacity: 53 liter (each side)  USE  NORMAL  PRODUCT RECOMMENDATION 1  Multifleet SCD 30  HYDRAULIC SYSTEM  Capacity: 329 liter  USE  NORMAL  PRODUCT RECOMMENDATION 1  Gear Oil Alcat 30  Check every 3 months/ 500 hours, changes	nge every 12 months/ 2000 hours	CLIMATE Mediterranean  CLIMATE

Check every 3 months/ 500 hours, change every 12 months/ 2000 hours

## CATERPILLAR TRACKED EXCAVATORS 235 83X (1973-1986)



GREASE POINTS/NIPPLES		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

COOLING SYSTEM Capacity: 44 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 17	

Check every 3 months/ 500 hours, change every 12 months/ 2000 hours

CLAMSHELL ROTATOR GEAR DRIVE		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		

PUMP DRIVE Capacity: 6,6 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Multifleet SCD 30	
Change every 2000 hours/12 months	

SWING GEAR Capacity: 38 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Multifleet SCD 30	
Check every 12 months/ 2000 hours	

## CATERPILLAR TRACKED EXCAVATORS 235 83X (1973-1986)



SWING REDUCTION UNIT Capacity: 34 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Multifleet SCD 30	
Check every 1 months/ 250 hours	

TRACK PINS	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Multifleet SCD 30	

TRACK ROLLERS & IDLERS		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.