

CATERPILLAR TRACKED EXCAVATORS

312B L 8JR (1996-2000)



ENGINE 3064T
Capacity: 13 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Change every 250 hours/ 1 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Synfleet SHPD 10W-40	Multifleet SHPD 10W-40	

Change every 250 hours/ 1 months

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Change every 100 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Synfleet SHPD 10W-40	Multifleet SHPD 10W-40	

Change every 100 hours

CATERPILLAR TRACKED EXCAVATORS

312B L 8JR (1996-2000)



FINAL DRIVES

Capacity: 2,5 liter (each hub)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	

Check every 1 months/ 250 hours, change every 12 months/ 2000 hours

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		

Check every 1 months/ 250 hours, change every 12 months/ 2000 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	

Change every 250 hours

USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		

Change every 250 hours

HYDRAULIC SYSTEM

Capacity: 162 liter (System), Capacity: 98 liter (Tank)

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		

Change every 2000 hours/ 12 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Agridiesel CRD+ 15W-40	Agrifluid Synth XHP Ultra

Change every 2000 hours/ 12 months

CATERPILLAR TRACKED EXCAVATORS

312B L 8JR (1996-2000)



USE		CLIMATE
50% use of breaker		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		

Change every 1000 hours

USE		CLIMATE
50% use of breaker		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Agridiesel CRD+ 15W-40	Agrifluid Synth XHP Ultra

Change every 1000 hours

USE		CLIMATE
100% use of breaker		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		

Change every 600 hours

USE		CLIMATE
100% use of breaker		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Agridiesel CRD+ 15W-40	Agrifluid Synth XHP Ultra

Change every 600 hours

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

COOLING SYSTEM

Capacity: 1,5 liter (Reservoir), Capacity: 15,5 liter (System)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 17		

Change every 6000 hours/ 72 months

CATERPILLAR TRACKED EXCAVATORS

312B L 8JR (1996-2000)



SWING GEAR

Capacity: 6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Check every 12 months/ 2000 hours

SWING REDUCTION UNIT

Capacity: 2,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	

Check every 1 months/ 250 hours, change every 6 months/ 1000 hours

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		

Check every 1 months/ 250 hours, change every 6 months/ 1000 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	

Change every 250 hours

USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		

Change every 250 hours

TRACK IDLERS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		

CATERPILLAR TRACKED EXCAVATORS

312B L 8JR (1996-2000)



TRACK ROLLERS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.