## CATERPILLAR TRACKED EXCAVATORS 317B L 9WW (1996-2002)



| Normal                           |                          | Mediterranean            |
|----------------------------------|--------------------------|--------------------------|
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agridiesel CRD+ 15W-40           | Dieselfleet CD+ 15W-40   | Multifleet SHPD 15W-40   |
| Change every 250 hours/ 1 months |                          |                          |
| USE                              |                          | CLIMATE                  |
| Normal                           |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2 |                          |
| Synfleet SHPD 10W-40             | Multifleet SHPD 10W-40   |                          |
| Change every 250 hours/ 1 months |                          |                          |
| JSE                              |                          | CLIMATE                  |
| Initial service                  |                          | Mediterranean            |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agridiesel CRD+ 15W-40           | Dieselfleet CD+ 15W-40   | Multifleet SHPD 15W-40   |
| Change every 100 hours           |                          |                          |
| USE                              |                          | CLIMATE                  |
| Initial service                  |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2 |                          |
| Synfleet SHPD 10W-40             | Multifleet SHPD 10W-40   |                          |

## CATERPILLAR TRACKED EXCAVATORS 317B L 9WW (1996-2002)



| FINAL DRIVES  |                             |               |
|---|-----------------------------|---------------|
| Capacity: 2,5 liter (each hub)                                |                             | CLIMATE       |
| Normal  |                             | Moderate      |
| PRODUCT RECOMMENDATION 1                                      | PRODUCT RECOMMENDATION 2    | Moderate      |
| Gear Oil Alcat 30   | Gear Oil Alcat 50           |               |
| Check every 1 months/ 250 hours, change                       | every 12 months/ 2000 hours |               |
| USE   |                             | CLIMATE       |
| Normal  |                             | Arctic        |
| PRODUCT RECOMMENDATION 1                                      |                             |               |
| Gear Oil Alcat 10W  |                             |               |
| Check every 1 months/ 250 hours, change                       | every 12 months/ 2000 hours |               |
| USE   |                             | CLIMATE       |
| Initial service   |                             | Moderate      |
| PRODUCT RECOMMENDATION 1                                      | PRODUCT RECOMMENDATION 2    |               |
| Gear Oil Alcat 30   | Gear Oil Alcat 50           |               |
| Change every 250 hours  |                             |               |
| USE   |                             | CLIMATE       |
| Initial service   |                             | Arctic        |
| PRODUCT RECOMMENDATION 1                                      |                             |               |
| Gear Oil Alcat 10W  |                             |               |
| Change every 250 hours  |                             |               |
|   |                             |               |
| HYDRAULIC SYSTEM Capacity: 105 liter (Reservoir), Capacity: 1 | 88 liter (System)           |               |
| USE   |                             | CLIMATE       |
| Normal  |                             | Mediterranean |
| PRODUCT RECOMMENDATION 1                                      |                             |               |
| Gear Oil Alcat 30   |                             |               |

PRODUCT RECOMMENDATION 2

Agridiesel CRD+ 15W-40

Change every 2000 hours/ 12 months

PRODUCT RECOMMENDATION 1

Kroontrak CVT 10W-40

Change every 2000 hours/ 12 months

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 3

**Agrifluid Synth XHP Ultra** 

## **CATERPILLAR TRACKED EXCAVATORS 317B L 9WW** (1996-2002)



| GREASE POINTS/NIPPLES    |  |          |
|--------------------------|--|----------|
| USE                      |  | CLIMATE  |
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| MoS2 Grease EP 2         |  |          |

| COOLING SYSTEM Capacity: 1,5 liter (Reservoir), Capacity: 17,3 liter (System) |  |          |  |
|---|--|----------|--|
| USE   |  | CLIMATE  |  |
| Extended drain (max)  |  | Moderate |  |
| PRODUCT RECOMMENDATION 1  |  |          |  |
| Coolant SP 17   |  |          |  |
| 01  |  | I        |  |

Check every 1 months/ 250 hours, change every 72 months/ 6000 hours

| USE                      |                          | CLIMATE                  |
|--------------------------|--------------------------|--------------------------|
| Normal                   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Coolant SP 15+           | Coolant SP 12            | Coolant -38 Organic NF   |

Check every 1 months/ 250 hours, change every 24 months/ 3000 hours

| SWING GEAR<br>Capacity: 9,1 liter |                          |                          |
|-----------------------------------|--------------------------|--------------------------|
| USE                               |                          | CLIMATE                  |
| Normal                            |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1          | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease                     | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2    |
| Check every 12 months/ 2000 hour  | rs                       | ,                        |

## CATERPILLAR TRACKED EXCAVATORS 317B L 9WW (1996-2002)



| SWING REDUCTION UNIT<br>Capacity: 3 liter    |                              |          |
|--|------------------------------|----------|
| USE  |                              | CLIMATE  |
| Normal                                       |                              | Moderate |
| PRODUCT RECOMMENDATION 1                     | PRODUCT RECOMMENDATION 2     |          |
| Gear Oil Alcat 30                            | Gear Oil Alcat 50            |          |
| Check every 1 months/ 250 hours, change      | e every 6 months/ 1000 hours |          |
| USE  |                              | CLIMATE  |
| Normal                                       |                              | Arctic   |
| PRODUCT RECOMMENDATION 1                     |                              |          |
| Gear Oil Alcat 10W                           |                              |          |
| Check every 1 months/ 250 hours, change      | e every 6 months/ 1000 hours |          |
| USE  |                              | CLIMATE  |
| Initial service                              |                              | Moderate |
| PRODUCT RECOMMENDATION 1                     | PRODUCT RECOMMENDATION 2     |          |
| Gear Oil Alcat 30                            | Gear Oil Alcat 50            |          |
| Change every 250 hours                       |                              |          |
| USE  |                              | CLIMATE  |
| Initial service                              |                              | Arctic   |
| PRODUCT RECOMMENDATION 1  Gear Oil Alcat 10W |                              |          |
|  |                              |          |
| Change every 250 hours                       |                              |          |
| TRACK IDLERS                                 |                              |          |
| USE  |                              | CLIMATE  |
| Normal                                       |                              | Moderate |
| PRODUCT RECOMMENDATION 1                     |                              |          |
| Multifleet SCD 30                            |                              |          |
|  |                              |          |
| TRACK ROLLERS                                |                              |          |
| USE  |                              | CLIMATE  |
| Normal                                       |                              | Moderate |
| PRODUCT RECOMMENDATION 1                     |                              |          |
| Multifleet SCD 30                            |                              |          |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.