

# CATERPILLAR TRACKED EXCAVATORS

## 329D L (2009-2011)



**ENGINE** C7 Acert  
Capacity: 30 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agridiesel CRD+ 15W-40</b>	<b>Dieselfleet CD+ 15W-40</b>	<b>Multifleet SHPD 15W-40</b>

*Change every 500 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Synfleet SHPD 10W-40</b>	<b>Multifleet SHPD 10W-40</b>	

*Change every 500 hours*

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agridiesel CRD+ 15W-40</b>	<b>Dieselfleet CD+ 15W-40</b>	<b>Multifleet SHPD 15W-40</b>

*Change every 100 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Synfleet SHPD 10W-40</b>	<b>Multifleet SHPD 10W-40</b>	

*Change every 100 hours*

### FINAL DRIVES

Capacity: 6 liter (each side)

USE	CLIMATE
Flexible (max)	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gear Oil Alcat 30</b>	<b>Gear Oil Alcat 50</b>	

USE	CLIMATE
Flexible (max)	Arctic

PRODUCT RECOMMENDATION 1		
<b>Gear Oil Alcat 10W</b>		

# CATERPILLAR TRACKED EXCAVATORS

## 329D L (2009-2011)



### HYDRAULIC SYSTEM

Capacity: 145 liter (Hydraulic tank), Capacity: 310 liter (Total)

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
<b>Gear Oil Alcat 30</b>		

*Change every 2000 hours*

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak CVT 10W-40</b>	<b>Agridiesel CRD+ 15W-40</b>	<b>Agrifluid Synth XHP Ultra</b>

*Change every 2000 hours*

### GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>HT Q9 High Grade Grease</b>	<b>Labora Grease</b>	<b>MoS2 Grease EP 2</b>

### COOLING SYSTEM

Capacity: 30 liter

USE		CLIMATE
Extended drain (max)		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant SP 17</b>		

*Change every 12000 hours/ 72 months*

USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	<b>Coolant -38 Organic NF</b>

*Change every 24 months/ 3000 hours*

USE		CLIMATE
Acceptable		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	<b>Coolant -38 Organic NF</b>

*Change every 36 months/ 3000 hours*

# CATERPILLAR TRACKED EXCAVATORS

## 329D L (2009-2011)



### SWING REDUCTION UNIT

Capacity: 10 liter

USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gear Oil Alcat 30</b>	<b>Gear Oil Alcat 50</b>	

USE		CLIMATE
Flexible (max)		Arctic
PRODUCT RECOMMENDATION 1		
<b>Gear Oil Alcat 10W</b>		

### TRACK IDLERS

USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 30</b>		

### TRACK ROLLERS

USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 30</b>		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.