

# CATERPILLAR TRACKED EXCAVATORS

## 336E (2011 AND AFTER)



**ENGINE** C9.3 ATAAC  
Capacity: 32 liter

USE	CLIMATE
Preferred	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Agridiesel MSP 15W-40</b>	<b>Dieselfleet MSP 15W-40</b>

*Check every 10 hours, change every 3 months/ 500 hours*

USE	CLIMATE
Preferred	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Dieselfleet LSP Ultra 10W-30</b>	<b>Dieselfleet MSP 10W-30</b>

*Check every 10 hours, change every 3 months/ 500 hours*

USE	CLIMATE
Alternative (acceptable)	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Agrisynth MSP 10W-40</b>	<b>Dieselfleet MSP 15W-40</b>

*Check every 10 hours, change every 3 months/ 500 hours*

USE	CLIMATE
Alternative (acceptable)	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrisynth LSP Ultra FE 5W-30</b>	<b>Agridiesel MSP 15W-40</b>	<b>Dieselfleet LSP Ultra 10W-30</b>

*Check every 10 hours, change every 3 months/ 500 hours*

### HYDRAULIC SYSTEM

Capacity: 194 liter (Change capacity), Capacity: 175 liter (Hydraulic tank), Capacity: 380 liter (System)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Gear Oil Alcat 30</b>	

*Check every 10 hours, change every 2000 hours/ 12 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agridiesel CRD+ 15W-40</b>	<b>Agrifluid HT-Plus</b>	<b>Kroontrak MTH 10W-30</b>

*Check every 10 hours, change every 2000 hours/ 12 months*

# CATERPILLAR TRACKED EXCAVATORS

## 336E (2011 AND AFTER)



USE		CLIMATE
Partial hammer use (50%)		Mediterranean
PRODUCT RECOMMENDATION 1		
<b>Gear Oil Alcat 30</b>		
<i>Check every 10 hours, change every 1000 hours</i>		
USE		CLIMATE
Partial hammer use (50%)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agridiesel CRD+ 15W-40</b>	<b>Agrifluid HT-Plus</b>	<b>Kroontrak MTH 10W-30</b>
<i>Check every 10 hours, change every 1000 hours</i>		
USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1		
<b>Perlus Biosynth 46</b>		
<i>Check every 10 hours, change every 2000 hours/ 12 months</i>		
USE		CLIMATE
Biodegradable oil, partial hammer use (50%)		Moderate
PRODUCT RECOMMENDATION 1		
<b>Perlus Biosynth 46</b>		
<i>Check every 10 hours, change every 1000 hours</i>		
USE		CLIMATE
Full time hammer use (100%)		Mediterranean
PRODUCT RECOMMENDATION 1		
<b>Gear Oil Alcat 30</b>		
<i>Check every 10 hours, change every 600 hours</i>		
USE		CLIMATE
Full time hammer use (100%)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agridiesel CRD+ 15W-40</b>	<b>Agrifluid HT-Plus</b>	<b>Kroontrak MTH 10W-30</b>
<i>Check every 10 hours, change every 600 hours</i>		
USE		CLIMATE
Biodegradable oil, full time hammer use (100%)		Moderate
PRODUCT RECOMMENDATION 1		
<b>Perlus Biosynth 46</b>		
<i>Check every 10 hours, change every 600 hours</i>		

# CATERPILLAR TRACKED EXCAVATORS

## 336E (2011 AND AFTER)



### GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>HT Q9 High Grade Grease</b>	<b>Labora Grease</b>	<b>MoS2 Grease EP 2</b>

### COOLING SYSTEM

Capacity: 56 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Coolant SP 17</b>		

*Check every 10 hours, change every 72 months/ 12000 hours*

### PUMP DRIVE

Capacity: 0,65 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak MTH 10W-30</b>	<b>Synfleet SHPD 10W-40</b>	<b>Dieselfleet LSP Ultra 10W-30</b>

*Check every 500 hours, change every 36 months/ 5000 hours*

### SWING GEAR

Capacity: 29 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>HT Q9 High Grade Grease</b>	<b>Labora Grease</b>	<b>MoS2 Grease EP 2</b>

# CATERPILLAR TRACKED EXCAVATORS

## 336E (2011 AND AFTER)



### SWING REDUCTION UNIT

Capacity: 19 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gear Oil Alcat 30</b>	<b>Gear Oil Alcat 50</b>	

Check every 1 months/ 250 hours, change every 6 months/ 1000 hours

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
<b>Gear Oil Alcat 10W</b>		

Check every 1 months/ 250 hours, change every 6 months/ 1000 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gear Oil Alcat 30</b>	<b>Gear Oil Alcat 50</b>	

Change every 250 hours

USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1		
<b>Gear Oil Alcat 10W</b>		

Change every 250 hours

# CATERPILLAR TRACKED EXCAVATORS

## 336E (2011 AND AFTER)


**TRAVEL REDUCTION UNIT**

Capacity: 8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gear Oil Alcat 30</b>	<b>Gear Oil Alcat 50</b>	

*Check every 1 months/ 250 hours, change every 12 months/ 2000 hours*

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
<b>Gear Oil Alcat 10W</b>		

*Check every 1 months/ 250 hours, change every 12 months/ 2000 hours*

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gear Oil Alcat 30</b>	<b>Gear Oil Alcat 50</b>	

*Change every 250 hours*

USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1		
<b>Gear Oil Alcat 10W</b>		

*Change every 250 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*