

CATERPILLAR TRACKED EXCAVATORS

5110B L AAK (2000-2003)



ENGINE 3412E
Capacity: 83 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP 10W-40	Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40

Check every 10 hours, change every 1 months/ 250 hours

HYDRAULIC SYSTEM

Capacity: 891 liter (Hydraulic tank), Capacity: 1686 liter (System)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 30	Gear Oil Alcat 30	

Check every 10 hours, change every 24 months/ 4000 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Agrifluid HT-Plus	Kroontrak MTH 10W-30

Check every 10 hours, change every 24 months/ 4000 hours

USE	CLIMATE
Biodegradable oil	Moderate

PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		

Check every 10 hours, change every 24 months/ 4000 hours

GREASE POINTS/NIPPLES

We are unable to give a standard recommendation for this component. Please contact our service department.

COOLING SYSTEM

Capacity: 113 liter

USE	CLIMATE
Flexible (max)	Moderate

PRODUCT RECOMMENDATION 1		
Coolant SP 17		

Check every 10 hours, change every 72 months/ 12000 hours

CATERPILLAR TRACKED EXCAVATORS

5110B L AAK (2000-2003)

**SWING GEAR**

Capacity: 274 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

MoS2 Grease EP 2*Check every 12 months/ 2000 hours***SWING REDUCTION UNIT**

Capacity: 14 liter (each), Capacity: 38 liter (Total system volume)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 30

PRODUCT RECOMMENDATION 2

Gear Oil Alcat 50*Check every 1 months/ 250 hours, change every 6 months/ 1000 hours*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 10W*Check every 1 months/ 250 hours, change every 6 months/ 1000 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 30

PRODUCT RECOMMENDATION 2

Gear Oil Alcat 50*Change every 250 hours/ 6 months*

USE	CLIMATE
Initial service	Arctic

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 10W*Change every 250 hours/ 6 months*

CATERPILLAR TRACKED EXCAVATORS

5110B L AAK (2000-2003)



TRACK IDLERS

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1		
Multifleet SCD 40		

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		

TRACK ROLLERS

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1		
Multifleet SCD 40		

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		

CATERPILLAR TRACKED EXCAVATORS

5110B L AAK (2000-2003)


TRAVEL REDUCTION UNIT

Capacity: 22 liter (each)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	

Check every 1 months/ 250 hours, change every 6 months/ 1000 hours

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		

Check every 1 months/ 250 hours, change every 6 months/ 1000 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	

Change every 250 hours/ 6 months

USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		

Change every 250 hours/ 6 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.