PRODUCT RECOMMENDATION

# CATERPILLAR VIBRATORY COMPACTORS CB/CC/CD/CP/CS CB34B XW 425/472 (2013 AND AFTER)

**ENGINE** C2.2
Capacity: 10,6 liter

| USE | | CLIMATE |
|---|---|---|
| Preferred | | Mediterranean |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | |
| **Agrisynth MSP 10W-40** | **Dieselfleet MSP 15W-40** | |
| *Check every 10 hours, change every 500 hours/ 12 months* | | |

| USE | | CLIMATE |
|---|---|---|
| Preferred | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | **PRODUCT RECOMMENDATION 3** |
| **Agrisynth LSP Ultra 10W-40** | **Agridiesel MSP 15W-40** | **Armado Synth LSP Ultra 10W-40** |
| *Check every 10 hours, change every 500 hours/ 12 months* | | |

| USE | | CLIMATE |
|---|---|---|
| Fluid analysis, preferred | | Mediterranean |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | |
| **Agrisynth MSP 10W-40** | **Dieselfleet MSP 15W-40** | |
| *Check every 250 hours* | | |

| USE | | CLIMATE |
|---|---|---|
| Fluid analysis, preferred | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | **PRODUCT RECOMMENDATION 3** |
| **Agrisynth LSP Ultra 10W-40** | **Agridiesel MSP 15W-40** | **Armado Synth LSP Ultra 10W-40** |
| *Check every 250 hours* | | |

| USE | | CLIMATE |
|---|---|---|
| Alternative (acceptable) | | Mediterranean |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | |
| **Agridiesel MSP 15W-40** | **Dieselfleet MSP 15W-40** | |
| *Check every 10 hours, change every 500 hours/ 12 months* | | |

| USE | | CLIMATE |
|---|---|---|
| Alternative (acceptable) | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | **PRODUCT RECOMMENDATION 3** |
| **Armado Synth MSP 5W-40** | **Dieselfleet LSP Ultra 10W-30** | **Dieselfleet MSP 10W-30** |
| *Check every 10 hours, change every 500 hours/ 12 months* | | |

| USE | | CLIMATE |
|---|---|---|
| Fluid analysis, alternative | | Mediterranean |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | |
| **Agridiesel MSP 15W-40** | **Dieselfleet MSP 15W-40** | |
| *Check every 250 hours* | | |

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# CATERPILLAR VIBRATORY COMPACTORS CB/CC/CD/CP/CS CB34B XW 425/472 (2013 AND AFTER)

| USE | | CLIMATE |
|---|---|---|
| Fluid analysis, alternative | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | **PRODUCT RECOMMENDATION 3** |
| **Armado Synth MSP 5W-40** | **Dieselfleet LSP Ultra 10W-30** | **Dieselfleet MSP 10W-30** |
| *Check every 250 hours* | | |

## HYDRAULIC SYSTEM
Capacity: 22 liter (Hydraulic tank)

| USE | | CLIMATE |
|---|---|---|
| Preferred, extended | | Moderate |
| **PRODUCT RECOMMENDATION 1** | | |
| **Perlus Biosynth 46** | | |
| *Check every 10 hours, change every 18 months/ 3000 hours* | | |

| USE | | CLIMATE |
|---|---|---|
| Fluid analysis, preferred | | Moderate |
| **PRODUCT RECOMMENDATION 1** | | |
| **Perlus Biosynth 46** | | |
| *Check every 12 months/ 500 hours* | | |

| USE | | CLIMATE |
|---|---|---|
| Alternative (acceptable) | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | **PRODUCT RECOMMENDATION 3** |
| **Agrisynth MSP 10W-40** | **Agridiesel MSP 15W-40** | **Agridiesel CRD+ 15W-40** |
| *Check every 10 hours, change every 2000 hours/ 12 months* | | |

| USE | | CLIMATE |
|---|---|---|
| Fluid analysis, alternative | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | **PRODUCT RECOMMENDATION 3** |
| **Agrisynth MSP 10W-40** | **Agridiesel MSP 15W-40** | **Agridiesel CRD+ 15W-40** |
| *Check every 12 months/ 500 hours* | | |

## GREASE POINTS/NIPPLES

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | | |
| **MoS2 Grease EP 2** | | |
| *Check every 3 months/ 250 hours* | | |

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# CATERPILLAR VIBRATORY COMPACTORS CB/CC/CD/CP/CS CB34B XW 425/472 (2013 AND AFTER)

**COOLING SYSTEM**
Capacity: 13 liter

| USE | | CLIMATE |
|---|---|---|
| Fluid analysis, preferred | | Moderate |
| **PRODUCT RECOMMENDATION 1** | | |
| **Coolant SP 17** | | |

*Check every 12 months, change every 72 months/ 12000 hours*

| USE | | CLIMATE |
|---|---|---|
| Fluid analysis, initial (preferred) | | Moderate |
| **PRODUCT RECOMMENDATION 1** | | |
| **Coolant SP 17** | | |

*Check every 500 hours*

| USE | | CLIMATE |
|---|---|---|
| Fluid analysis, alternative | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | **PRODUCT RECOMMENDATION 3** |
| **Coolant SP 15+** | **Coolant SP 12** | **Coolant -38 Organic NF** |

*Check every 3 months/ 500 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367