PRODUCT RECOMMENDATION

CATERPILLAR VIBRATORY COMPACTORS CB/CC/CD/CP/CS CP-563C 4KN00929 ->

(1995-2000)

ENGINE 3116T

Capacity: 20 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Agridiesel CRD+ 15W-40	**Dieselfleet CD+ 15W-40**	**Multifleet SHPD 15W-40**

Check every 10 hours, change every 250 hours/ 3 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Synfleet SHPD 10W-40	**Multifleet SHPD 10W-40**	

Check every 10 hours, change every 250 hours/ 3 months

TRANSAXLE

Capacity: 27 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Agrifluid HT-Plus	**Kroontrak MTH 10W-30**	**Agrifluid HT**

Check every 3 months/ 250 hours, change every 12 months/ 1000 hours

HYDRAULIC SYSTEM

Capacity: 110 liter (Hydraulic tank)

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Multifleet SCD 30	**Gear Oil Alcat 30**	

Check every 10 hours, change every 1000 hours/ 12 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Agridiesel CRD+ 15W-40	**Agrifluid HT-Plus**	**Kroontrak MTH 10W-30**

Check every 10 hours, change every 1000 hours/ 12 months

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

CATERPILLAR VIBRATORY COMPACTORS CB/CC/CD/CP/CS CP-563C 4KN00929 ->

(1995-2000)

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

USE		CLIMATE
Light Duty		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
HT Q9 High Grade Grease	**Labora Grease**	

COOLING SYSTEM
Capacity: 33,1 liter

USE		CLIMATE
Preferred, extended		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 17		

Check every 10 hours, change every 72 months/ 6000 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Coolant SP 15+	**Coolant SP 12**	**Coolant -38 Organic NF**

Check every 10 hours, change every 24 months/ 3000 hours

DRUM COOLING
Capacity: 22,5 liter

USE		CLIMATE
At overhauls only		Mediterranean
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Multifleet SCD 30	**Gear Oil Alcat 30**	

USE		CLIMATE
At overhauls only		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Agridiesel CRD+ 15W-40	**Agrifluid HT-Plus**	**Kroontrak MTH 10W-30**

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

CATERPILLAR VIBRATORY COMPACTORS CB/CC/CD/CP/CS CP-563C 4KN00929 ->

(1995-2000)

ECCENTRIC WEIGHT HOUSING
Capacity: 55 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Abacot MEP HD 220		

Check every 3 months/ 250 hours, change every 12 months/ 1000 hours

FINAL DRIVE - DRUM
Capacity: 3,2 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 50		

Check every 3 months/ 250 hours, change every 12 months/ 1000 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Abacot MEP Synth 220		

Check every 3 months/ 250 hours, change every 12 months/ 1000 hours

VIBRATORY SUPPORT
Capacity: 0,85 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	**Unigear LS GL-3/GL-5 85W-140**	

Check every 3 months/ 250 hours, change every 12 months/ 1000 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	**Gearlube HS GL-5 80W-140**

Check every 3 months/ 250 hours, change every 12 months/ 1000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367