## CATERPILLAR VIBRATORY COMPACTORS CB/CC/CD/CP/CS CS-583 1EL/8YJ



Mediterranean
DN 2
CLIMATE
Moderate
DN 2 PRODUCT RECOMMENDATION 3
V-30 Synfleet SHPD 10W-40
CLIMATE
Cold
C

DIFFERENTIAL Capacity: 16,1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
Check every 1 months/ 250 hours, change every 12 months/ 2000 hours		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
Change every 100 hours		

## CATERPILLAR VIBRATORY COMPACTORS CB/CC/CD/CP/CS CS-583 1EL/8YJ



TRANSFERBOX Capacity: 0,5 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Agrifluid HT			
Check every 1 months/ 250 hours, change every 12 months/ 2000 hours			
USE		CLIMATE	
Initial service		Moderate	
PRODUCT RECOMMENDATION 1			
Agrifluid HT			
Change every 100 hours			

HYDRAULIC SYSTEM Capacity: 132,6 liter (Hydraulic tank)		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 30	Gear Oil Alcat 30	

Check every 10 hours, change every 2000 hours/12 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40

Check every 10 hours, change every 2000 hours/ 12 months

GREASE POINTS/NIPPLES	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
MoS2 Grease EP 2	

COOLING SYSTEM Capacity: 36,4 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	
Check every 10 hours, change every 24 months/ 3000 hours		

## CATERPILLAR VIBRATORY COMPACTORS CB/CC/CD/CP/CS CS-583 1EL/8YJ



DRUM SUPPORT BEARING Capacity: 2 liter		
use Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 Abacot MEP HD 220		
	_ , , , , , , , , , , , , , , , , , , ,	

Check every 1 months/ 250 hours, change every 6 months/ 1000 hours

WEIGHT SHAFT BEARING Capacity: 49 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Abacot MEP HD 220		
01 1 4 4 40501	0 4 4 4000 4	

Check every 1 months/ 250 hours, change every 6 months/ 1000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.