## **CATERPILLAR WHEELED EXCAVATORS**214B



ENGINE Capacity: 15 liter				
USE		CLIMATE		
Normal		Mediterranean		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Multifleet SCD 40	Multifleet SCD 30			
Change every 250 hours/ 1 months				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40		
Change every 250 hours/ 1 months				
USE		CLIMATE		
Normal		Cold		
PRODUCT RECOMMENDATION 1				
Multifleet SCD 10W				
Change every 250 hours/ 1 months				

DIFFERENTIAL STEERED AXLE Capacity: 10 liter			
USE	CLIMATE		
Normal	Moderate		
PRODUCT RECOMMENDATION 1			
Gearlube LS 80W-90			
Check every 500 hours, change eve	s/ 1000 hours		

HUB REDUCTIONS Capacity: 2,5 liter (each hub)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Change every 1000 hours/ 6 months	

## CATERPILLAR WHEELED EXCAVATORS 214B



TRANSAXLE Capacity: 15 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Change every 1000 hours/ 6 months	
HYDRAULIC SYSTEM Capacity: 330 liter	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Multifleet SCD 30	
Change every 2000 hours/ 12 months	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 10W	
Change every 2000 hours/ 12 months	
GREASE POINTS/NIPPLES	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
MoS2 Grease EP 2	
COOLING SYSTEM	
Capacity: 30 liter	
USE	 CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 17	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Change every 2000 hours/ 12 months