CATERPILLAR WHEELED EXCAVATORS 224B



Normal PRODUCT RECOMMENDATION 1 Multifleet SCD 40 Change every 250 hours/ 1 months USE Normal PRODUCT RECOMMENDATION 2 Multifleet SCD 30 CLIMATE Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Kroontrak MTH 10W-30 Change every 250 hours/ 1 months USE Normal Change every 250 hours/ 1 months USE Normal Change every 250 hours/ 1 months USE Normal Multifleet SCD 10W	ENGINE Capacity: 15 liter		
Multifleet SCD 40 Change every 250 hours/ 1 months USE Normal PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 PRODUCT RECOMMENDATION 3 PRODUCT RECOMMENDATION 3 PRODUCT RECOMMENDATION 3 Dieselfleet CD+ 15W-40 Change every 250 hours/ 1 months USE Normal PRODUCT RECOMMENDATION 1 CLIMATE Cold PRODUCT RECOMMENDATION 1	USE		CLIMATE
Multifleet SCD 40 Change every 250 hours/ 1 months USE Normal PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Synfleet SHPD 10W-40 Change every 250 hours/ 1 months USE Normal PRODUCT RECOMMENDATION 2 Change every 250 hours/ 1 months USE Normal PRODUCT RECOMMENDATION 1 Cold PRODUCT RECOMMENDATION 1	Normal		Mediterranean
Change every 250 hours/ 1 months USE Normal PRODUCT RECOMMENDATION 1 Kroontrak MTH 10W-30 Change every 250 hours/ 1 months USE Normal PRODUCT RECOMMENDATION 2 Change every 250 hours/ 1 months USE Normal PRODUCT RECOMMENDATION 1 Cold PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Normal PRODUCT RECOMMENDATION 1 Kroontrak MTH 10W-30 Change every 250 hours/ 1 months USE Normal PRODUCT RECOMMENDATION 2 Synfleet SHPD 10W-40 Climate CLIMATE CLIMATE CLIMATE Cold PRODUCT RECOMMENDATION 3 Dieselfleet CD+ 15W-40 CLIMATE Cold	Multifleet SCD 40	Multifleet SCD 30	
Normal PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Synfleet SHPD 10W-40 Change every 250 hours/ 1 months USE Normal PRODUCT RECOMMENDATION 1 CLIMATE Cold	Change every 250 hours/ 1 months		
PRODUCT RECOMMENDATION 1 Kroontrak MTH 10W-30 Synfleet SHPD 10W-40 Dieselfleet CD+ 15W-40 Change every 250 hours/ 1 months USE Normal PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 1	USE		CLIMATE
Kroontrak MTH 10W-30 Change every 250 hours/ 1 months USE Normal PRODUCT RECOMMENDATION 1 Synfleet SHPD 10W-40 Dieselfleet CD+ 15W-40 CLIMATE COId	Normal		Moderate
Change every 250 hours/ 1 months USE CLIMATE Normal Cold PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
USE CLIMATE Normal Cold PRODUCT RECOMMENDATION 1	Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40
Normal Cold PRODUCT RECOMMENDATION 1	Change every 250 hours/ 1 months		·
PRODUCT RECOMMENDATION 1	USE		CLIMATE
	Normal		Cold
Multifleet SCD 10W	PRODUCT RECOMMENDATION 1		
	Multifleet SCD 10W		
Change every 250 hours/ 1 months	Change every 250 hours/ 1 months		

DIFFERENTIAL STEERED AXLE Capacity: 10,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Check every 500 hours, change ever	ours

HUB REDUCTIONS Capacity: 2,5 liter (each hub)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Change every 1000 hours/ 12 months	

CATERPILLAR WHEELED EXCAVATORS 224B



TRANSAXLE Capacity: 13,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Change every 1000 hours/ 12 months	
HYDRAULIC SYSTEM Capacity: 390 liter	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Multifleet SCD 30	
Change every 2000 hours/ 12 months	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 10W	
Change every 2000 hours/ 12 months	
GREASE POINTS/NIPPLES	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
MoS2 Grease EP 2	
COOLING SYSTEM	
Capacity: 30 liter	
USE	 CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Coolant SP 17

Change every 2000 hours/ 12 months