

# CATERPILLAR WHEELED LOADERS 914K CD2 (2014 AND AFTER)



**ENGINE** C3.8 Tier 4i  
Capacity: 13,3 liter

USE	CLIMATE
Fluid analysis, preferred	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Agrisynth MSP 10W-40</b>	<b>Dieselfleet MSP 15W-40</b>

*Check every 250 hours*

USE	CLIMATE
Fluid analysis, preferred	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agridiesel MSP 15W-40</b>	<b>Dieselfleet LSP Ultra 10W-30</b>	<b>Dieselfleet MSP 10W-30</b>

*Check every 250 hours*

USE	CLIMATE
Alternative (acceptable)	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Agrisynth MSP 10W-40</b>	<b>Dieselfleet MSP 15W-40</b>

*Check every 10 hours, change every 500 hours/ 12 months*

USE	CLIMATE
Alternative (acceptable)	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agridiesel MSP 15W-40</b>	<b>Dieselfleet LSP Ultra 10W-30</b>	<b>Dieselfleet MSP 10W-30</b>

*Check every 10 hours, change every 500 hours/ 12 months*

**DIFFERENTIAL FRONT**  
Capacity: 7,5 liter

USE	CLIMATE
Fluid analysis, preferred	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrifluid HT-Plus</b>	<b>Kroontrak MTH 10W-30</b>	<b>Agrifluid HT</b>

*Check every 500 hours*

USE	CLIMATE
Alternative (acceptable)	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrifluid HT-Plus</b>	<b>Kroontrak MTH 10W-30</b>	<b>Agrifluid HT</b>

*Check every 1 months/ 250 hours, change every 6 months/ 1000 hours*

# CATERPILLAR WHEELED LOADERS 914K CD2 (2014 AND AFTER)



## DIFFERENTIAL REAR

Capacity: 7,5 liter

USE		CLIMATE
Fluid analysis, preferred		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrifluid HT-Plus</b>	<b>Kroontrak MTH 10W-30</b>	<b>Agrifluid HT</b>

Check every 500 hours

USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrifluid HT-Plus</b>	<b>Kroontrak MTH 10W-30</b>	<b>Agrifluid HT</b>

Check every 1 months/ 250 hours, change every 6 months/ 1000 hours

## FINAL DRIVES

Capacity: 2,2 liter (each)

USE		CLIMATE
Fluid analysis, preferred		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrifluid HT-Plus</b>	<b>Kroontrak MTH 10W-30</b>	<b>Agrifluid HT</b>

Check every 500 hours

USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrifluid HT-Plus</b>	<b>Kroontrak MTH 10W-30</b>	<b>Agrifluid HT</b>

Check every 1 months/ 250 hours, change every 6 months/ 1000 hours

## TRANSMISSION HYDROSTATIC

Capacity: 3,2 liter

USE		CLIMATE
Fluid analysis, preferred		Moderate
PRODUCT RECOMMENDATION 1		
<b>Gear Oil Alcat 10W</b>		

Check every 500 hours

USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1		
<b>Gear Oil Alcat 10W</b>		

Check every 1 months/ 250 hours, change every 6 months/ 1000 hours

# CATERPILLAR WHEELED LOADERS 914K CD2 (2014 AND AFTER)



## HYDRAULIC SYSTEM

Capacity: 85 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

## CENTRAL LUBRICATION SYSTEM

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**MoS2 Grease EP 2**

## EXTERNAL GREASE POINTS

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**MoS2 Grease EP 2**

## GREASE POINTS/NIPPLES DRIVE SHAFT

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**HT Q9 High Grade Grease**

*Check every 1 months/ 250 hours*

## GREASE POINTS/NIPPLES STEERING COLUMN

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**HT Q9 High Grade Grease**

# CATERPILLAR WHEELED LOADERS 914K CD2 (2014 AND AFTER)



## COOLING SYSTEM

Capacity: 15 liter

USE		CLIMATE
Fluid analysis, preferred		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant SP 17</b>		

*Check every 12 months, change every 72 months/ 12000 hours*

USE		CLIMATE
Fluid analysis, initial (preferred)		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant SP 17</b>		

*Check every 500 hours*

USE		CLIMATE
Fluid analysis, alternative		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	<b>Coolant -38 Organic NF</b>

*Check every 500 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*