JCB BACKHOE LOADERS 3CX (55 KW) 2WD JCB ECOMAX T4I (2010-2015)



ENGINE JCB Ecomax T4i Capacity: 12-15 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

DIFFERENTIAL REAR 2WS Capacity: 21 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
Observe and the AFOO beauty of the AFOO beauty of the AFOO beauty		

Check every 6 months/ 500 hours, change every 12 months/ 1000 hours

TRANSMISSION SynchroShuttle Capacity: 10 liter (Change capacity), Capacity: 14,4 liter (Dry fill)		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Check every 50 hours, change every 1000 hours/ 12 months		

USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 10W	

Check every 50 hours, change every 1000 hours/12 months

HYDRAULIC SYSTEM Capacity: 130 liter		
USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	Perlus AF 46	
01 1 101	20001 /24 //	

Check every 10 hours, change every 2000 hours/24 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 32	Perlus AF 32	
Check every 10 hours, change every 2000 hours/ 24 months		

Check every 10 hours, change every 2000 hours/24 months

JCB BACKHOE LOADERS 3CX (55 KW) 2WD JCB ECOMAX T4I (2010-2015)



HYDRAULIC BRAKE SYSTEM Capacity: 1,4 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 15		
Check avery 10 hours, change avery 2000 hours/24 months		

Check every 10 hours, change every 2000 hours/ 24 months

GREASE POINTS/NIPPLES			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
HT Q9 High Grade Grease	Labora Grease		

COOLING SYSTEM Capacity: 17,5 liter (Change capacity), Capacity: 18,5 liter (Dry fill)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
Check every 10 hours change eve	ry 2000 hours/24 months	

Check every 10 hours, change every 2000 hours/24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.