

# JCB HIGH MOBILITY VEHICLES FASTRAC 1115



## ENGINE Perkins 1000T

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Dieselfleet CD+ 15W-40</b>	<b>Multifleet SHPD 15W-40</b>	

*Change every 250 hours/ 1 months*

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Dieselfleet CD+ 15W-40</b>	<b>Multifleet SHPD 15W-40</b>	

*Change every 100 hours*

## DIFFERENTIAL FRONT

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

*Change every 1000 hours/ 12 months*

## DIFFERENTIAL REAR

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

*Change every 1000 hours/ 12 months*

## HUB REDUCTIONS FRONT

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

*Change every 1000 hours/ 12 months*

# JCB HIGH MOBILITY VEHICLES FASTRAC 1115



## TRANSFERBOX/P.T.O. FRONT

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

*Change every 1000 hours/ 12 months*

## HYDRAULIC SYSTEM

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
<b>Perlus H 32</b>		

*Change every 2000 hours/ 24 months*

## HYDRAULIC CLUTCH SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Drauliquid-S DOT 4</b>		

*Change every 2000 hours/ 24 months*

## GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>HT Q9 High Grade Grease</b>		

## POWER TAKE OFF GEARBOX

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Kroontrak MTH 10W-30</b>		

*Change every 1000 hours/ 12 months*

# JCB HIGH MOBILITY VEHICLES FASTRAC 1115



## RANGE GEARBOX

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Kroontrak MTH 10W-30</b>		

*Change every 1000 hours/ 12 months*

## SPEED GEARBOX SINGLE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Kroontrak MTH 10W-30</b>		

*Change every 1000 hours/ 12 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*