PRODUCT RECOMMENDATION

JCB SKID STEER LOADERS 260 JCB ECOMAX TCAE-55 (STAGE IIIB/T4F) (2014-2018)

ENGINE JCB Ecomax T4f (SCR)
Capacity: 14 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Agrisynth LSP Ultra FE 5W-30	**Armado Synth LSP Ultra 5W-30**	**Dieselfleet MSP 10W-30**

Check every 10 hours, change every 500 hours/ 6 months

HYDRAULIC SYSTEM
Capacity: 60 liter (Hydraulic system including tank)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Perlus Biosynth 46	**Perlus H 46**	

USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
HT Q9 High Grade Grease	**Labora Grease**	

COOLING SYSTEM
Capacity: 15,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Coolant SP 15+	**Coolant SP 12**	**Coolant -38 Organic NF**

Check every 10 hours, change every 2000 hours/ 24 months

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

JCB SKID STEER LOADERS 260 JCB ECOMAX TCAE-55 (STAGE IIIB/T4F) (2014-2018)

DRIVE CHAIN CASE
Capacity: 11,7 liter (each side)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel MSP 15W-40	**Agridiesel CRD+ 15W-40**	**Dieselfleet CD+ 15W-40**

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367