PRODUCT RECOMMENDATION

# JCB TELESCOPIC HANDLERS (USA) LOADALL/AGRI 527-58 USA (81 KW) STAGE IIIB/T4I (2014 AND AFTER)

**ENGINE** JCB Ecomax T4i
Capacity: 15 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| **Armado Synth MSP 5W-40** | | |

*Check every 10 hours, change every 500 hours/ 6 months*

**DIFFERENTIAL FRONT**
Capacity: 17,7 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| **Agrifluid HT** | | |

*Check every 50 hours, change every 6 months/ 500 hours*

**DIFFERENTIAL REAR**
Capacity: 10 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| **Agrifluid HT** | | |

*Check every 50 hours, change every 6 months/ 500 hours*

**HUB REDUCTIONS FRONT**
Capacity: 1,9 liter (each hub)

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| **Agrifluid HT** | | |

*Check every 1 months/ 100 hours, change every 12 months/ 1000 hours*

**HUB REDUCTIONS REAR**
Capacity: 2 liter (each hub)

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| **Agrifluid HT** | | |

*Check every 1 months/ 100 hours, change every 12 months/ 1000 hours*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# JCB TELESCOPIC HANDLERS (USA) LOADALL/AGRI 527-58 USA (81 KW) STAGE IIIB/T4I (2014 AND AFTER)

**TRANSMISSION** Synchro Shuttle SS700/750
Capacity: 11,5 liter (Change capacity), Capacity: 13,5 liter (Dry fill)

| USE | CLIMATE |
|---|---|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | | |
|---|---|---|
| **Gear Oil Alcat 30** | | |

*Check every 10 hours, change every 1000 hours/ 12 months*

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|---|---|---|
| **Gear Oil Alcat 10W** | | |

*Check every 10 hours, change every 1000 hours/ 12 months*

**TRANSMISSION POWERSHIFT** PS760
Capacity: 21 liter (Change capacity), Capacity: 23 liter (Dry fill)

| USE | CLIMATE |
|---|---|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | | |
|---|---|---|
| **Gear Oil Alcat 30** | | |

*Check every 10 hours, change every 1000 hours/ 12 months*

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|---|---|---|
| **Gear Oil Alcat 10W** | | |

*Check every 10 hours, change every 1000 hours/ 12 months*

**HYDRAULIC SYSTEM**
Capacity: 116 liter (Hydraulic tank)

| USE | CLIMATE |
|---|---|
| Normal | Tropical |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **Perlus H 46** | **Perlus AF 46** | |

*Check every 50 hours, change every 2000 hours/ 24 months*

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **Perlus H 32** | **Perlus AF 32** | |

*Check every 50 hours, change every 2000 hours/ 24 months*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# JCB TELESCOPIC HANDLERS (USA) LOADALL/AGRI 527-58 USA (81 KW) STAGE IIIB/T4I (2014 AND AFTER)

## HYDRAULIC BRAKE SYSTEM

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | | |
| **Perlus H 15** | | |

*Check every 10 hours, change every 2000 hours/ 24 months*

## GREASE POINTS/NIPPLES

| USE | | CLIMATE |
|---|---|---|
| Preferred | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | |
| **HT Q9 High Grade Grease** | **Labora Grease** | |

## COOLING SYSTEM
Capacity: 28 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | **PRODUCT RECOMMENDATION 3** |
| **Coolant SP 15+** | **Coolant SP 12** | **Coolant -38 Organic NF** |

*Check every 10 hours, change every 2000 hours/ 24 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367