

# JCB TELESCOPIC HANDLERS (USA)

## LOADALL/AGRI 535-125 HIVIZ USA (93 KW)

### STAGE IIIB/T4I (2014 AND AFTER)



**ENGINE** JCB Ecomax T4i  
Capacity: 15 liter

| USE    | CLIMATE      |
|--------|--------------|
| Normal | All climates |

PRODUCT RECOMMENDATION 1

**Armado Synth MSP 5W-40**

*Check every 10 hours, change every 500 hours/ 6 months*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Agrisynt LSP Ultra FE 5W-30**

PRODUCT RECOMMENDATION 2

**Armado Synth LSP Ultra 5W-30**

PRODUCT RECOMMENDATION 3

**Dieselfleet MSP 10W-30**

*Check every 10 hours, change every 500 hours/ 6 months*

**DIFFERENTIAL FRONT**  
Capacity: 17,7 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Agrifluid HT**

*Check every 50 hours, change every 6 months/ 500 hours*

**DIFFERENTIAL REAR**  
Capacity: 17,7 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Agrifluid HT**

*Check every 50 hours, change every 6 months/ 500 hours*

**HUB REDUCTIONS FRONT**  
Capacity: 1,9 liter (each hub)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Agrifluid HT**

*Check every 50 hours, change every 6 months/ 500 hours*

# JCB TELESCOPIC HANDLERS (USA)

## LOADALL/AGRI 535-125 HIVIZ USA (93 KW)

### STAGE IIIB/T4I (2014 AND AFTER)

**HUB REDUCTIONS REAR**

Capacity: 2 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Agrifluid HT***Check every 50 hours, change every 6 months/ 500 hours***TRANSMISSION POWERSHIFT PS760**

Capacity: 21 liter (Change capacity), Capacity: 23 liter (Dry fill)

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 30***Check every 10 hours, change every 1000 hours/ 12 months*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 10W***Check every 10 hours, change every 1000 hours/ 12 months***HYDRAULIC SYSTEM**

Capacity: 127 liter (Hydraulic tank)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Perlus Biosynth 46**

PRODUCT RECOMMENDATION 2

**Perlus H 46***Check every 50 hours, change every 2000 hours/ 24 months***HYDRAULIC BRAKE SYSTEM**

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Perlus H 15***Check every 10 hours, change every 2000 hours/ 24 months*

# JCB TELESCOPIC HANDLERS (USA)

## LOADALL/AGRI 535-125 HIVIZ USA (93 KW)

### STAGE IIIB/T4I (2014 AND AFTER)



#### GREASE POINTS/NIPPLES

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**HT Q9 High Grade Grease**

#### COOLING SYSTEM

Capacity: 28 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**Coolant SP 15+**

PRODUCT RECOMMENDATION 2

**Coolant SP 12**

PRODUCT RECOMMENDATION 3

**Coolant -38 Organic NF**

*Check every 10 hours, change every 2000 hours/ 24 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*