

JCB TELESCOPIC HANDLERS TM320 ECOMAX T4F (SCR) (2014 AND AFTER)



ENGINE JCB Ecomax T4f (SCR)
Capacity: 15 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-------------------------------------|-------------------------------------|-------------------------------|
| Agrisynth LSP Ultra FE 5W-30 | Armado Synth LSP Ultra 5W-30 | Dieselfleet MSP 10W-30 |

Check every 10 hours, change every 500 hours/ 6 months

DIFFERENTIAL FRONT
Capacity: 17,7 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| Agrifluid HT | | |

Change every 500 hours/ 12 months

DIFFERENTIAL REAR
Capacity: 17,7 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| Agrifluid HT | | |

Change every 500 hours/ 12 months

TRANSFERBOX
Capacity: 1,3 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|-----------------------------|--|--|
| Gearlube GL-5 80W-90 | | |

Check every 6 months/ 500 hours, change every 12 months/ 1000 hours

JCB TELESCOPIC HANDLERS TM320 ECOMAX T4F (SCR) (2014 AND AFTER)

**TRANSMISSION POWERSHIFT PS760 6/4 6/4**

Capacity: 19 liter (Dry fill)

| USE | | CLIMATE |
|--------------------------|--|---------------|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 30 | | |

Check every 6 months/ 500 hours, change every 12 months/ 1000 hours

| USE | | CLIMATE |
|---------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 10W | | |

*Check every 6 months/ 500 hours, change every 12 months/ 1000 hours***HYDRAULIC SYSTEM**

Capacity: 97 liter (Hydraulic tank), Capacity: 135 liter (System)

| USE | | CLIMATE |
|---------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Perlus Biosynth 46 | Perlus H 46 | |

Check every 10 hours, change every 1000 hours/ 12 months

| USE | | CLIMATE |
|---------------------------|--|----------|
| Biodegradable oil | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Perlus Biosynth 46 | | |

*Check every 10 hours, change every 1000 hours/ 12 months***GREASE POINTS/NIPPLES**

| USE | | CLIMATE |
|--------------------------|---------------------------------|------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

COOLING SYSTEM

Capacity: 20,5 liter

| USE | | CLIMATE |
|--------------------------|--------------------------|-------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Coolant SP 15+ | Coolant SP 12 | Coolant -38 Organic NF |

*Check every 10 hours, change every 2000 hours/ 24 months**The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products.*

JCB TELESCOPIC HANDLERS TM320 ECOMAX T4F (SCR) (2014 AND AFTER)



Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.