

JCB WHEELED LOADERS 403 (2000-2007)

ENGINE Deutz D 2009 L03
Capacity: 5,8 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40

Check every 10 hours, change every 1000 hours/ 12 months

USE		CLIMATE
Severe		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40

Check every 10 hours, change every 250 hours/ 3 months

USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40

Check every 10 hours, change every 500 hours/ 6 months

HYDRAULIC SYSTEM
Capacity: 40 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Synfleet SHPD 10W-40	Armado Synth 5W-30	Multifleet SHPD 10W-40

Check every 10 hours, change every 1000 hours/ 12 months

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
HT Q9 High Grade Grease		

JCB WHEELED LOADERS 403 (2000-2007)**COOLING SYSTEM**

Capacity: 6,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 10 hours, change every 2000 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.