

KUBOTA TRACKED EXCAVATORS

K/KH/KX/U KX91-3S2 KUBOTA D1703-M-E3-BH (TIER 4I) (2007-2011)



ENGINE Kubota D1703-M-E3B
Capacity: 5,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40

Change every 250 hours/ 6 months

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40

Change every 50 hours

HYDRAULIC SYSTEM

Capacity: 36 liter (Hydraulic tank), Capacity: 55 liter (System)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Perlus H 46	Perlus H 68	Perlus AF 46

Check every 10 hours, change every 1000 hours

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Perlus H 32	Perlus AF 32

Check every 10 hours, change every 1000 hours

USE	CLIMATE
Breaker use 40 - 60%	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Perlus H 46	Perlus H 68	Perlus AF 46

Check every 10 hours, change every 400 hours

USE	CLIMATE
Breaker use 40 - 60%	Cold

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Perlus H 32	Perlus AF 32

Check every 10 hours, change every 400 hours

KUBOTA TRACKED EXCAVATORS

K/KH/KX/U KX91-3S2 KUBOTA D1703-M-E3-BH (TIER 4I) (2007-2011)



USE		CLIMATE
Breaker use 60 - 80%		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Perlus H 46	Perlus H 68	Perlus AF 46

Check every 10 hours, change every 300 hours

USE		CLIMATE
Breaker use 60 - 80%		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 32	Perlus AF 32	

Check every 10 hours, change every 300 hours

USE		CLIMATE
Breaker use > 80%		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Perlus H 46	Perlus H 68	Perlus AF 46

Check every 10 hours, change every 200 hours

USE		CLIMATE
Breaker use > 80%		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 32	Perlus AF 32	

Check every 10 hours, change every 200 hours

USE		CLIMATE
Breaker use 20 - 40%		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Perlus H 46	Perlus H 68	Perlus AF 46

Check every 10 hours, change every 800 hours

USE		CLIMATE
Breaker use 20 - 40%		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 32	Perlus AF 32	

Check every 10 hours, change every 800 hours

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

KUBOTA TRACKED EXCAVATORS

K/KH/KX/U KX91-3S2 KUBOTA D1703-M-E3-BH (TIER 4I) (2007-2011)

**COOLING SYSTEM**

Capacity: 7,3 liter (Radiator), Capacity: 1,6 liter (Reserve tank)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

*Change every 24 months***TRAVEL REDUCTION UNIT**

Capacity: 0,6 liter

USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube HS GL-5 80W-140	Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140

Change every 500 hours/ 12 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 500 hours/ 12 months

USE		CLIMATE
Initial service		Tropical
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube HS GL-5 80W-140	Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140

Change every 100 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 100 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.