

KUBOTA UTILITY VEHICLES RTV RTV-900W-EU

**ENGINE**

Capacity: 3,1 liter, Filter capacity: 0,4 liter

USE

Normal

CLIMATE

Tropical

PRODUCT RECOMMENDATION 1**Multifleet SCD 30***Change every 100 hours***USE**

Normal

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1**Multifleet SCD 20W-20***Change every 100 hours***USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Kroontrak CVT 10W-40****PRODUCT RECOMMENDATION 2****Kroontrak MTH 10W-30****PRODUCT RECOMMENDATION 3****Synfleet SHPD 10W-40***Change every 100 hours***USE**

Normal

CLIMATE

Arctic

PRODUCT RECOMMENDATION 1**Multifleet SCD 10W***Change every 100 hours***USE**

Initial service

CLIMATE

Tropical

PRODUCT RECOMMENDATION 1**Multifleet SCD 30***Change every 50 hours***USE**

Initial service

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1**Multifleet SCD 20W-20***Change every 50 hours***USE**

Initial service

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Kroontrak CVT 10W-40****PRODUCT RECOMMENDATION 2****Kroontrak MTH 10W-30****PRODUCT RECOMMENDATION 3****Synfleet SHPD 10W-40***Change every 50 hours*

KUBOTA UTILITY VEHICLES RTV RTV-900W-EU



USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
<i>Change every 50 hours</i>		

DIFFERENTIAL FRONT Capacity: 0,6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
<i>Change every 200 hours</i>		

KNUCKLE CASE Capacity: 0,15 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
<i>Change every 400 hours</i>		

TRANSMISSION Capacity: 10 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
<i>Change every 200 hours</i>		

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
<i>Change every 50 hours</i>		



KUBOTA UTILITY VEHICLES RTV RTV-900W-EU



HYDRAULIC BRAKE SYSTEM

Capacity: 0,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3*Change every 24 months*

POWER STEERING

Capacity: 5,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agrifluid HT*Change every 200 hours*

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2

COOLING SYSTEM

Capacity: 4 liter (+ recovery tank)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF

PRODUCT RECOMMENDATION 2

Coolant -26*Change every 24 months*

HYDRAULIC LIFT SYSTEM

Capacity: 8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agrifluid HT*Change every 200 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.