PRODUCT RECOMMENDATION

MANITOU MANISCOPIC MLT MLT 526 TURBO SERIES 1 PERKINS 1004.4T (1994-1996)

ENGINE Perkins 1004-4T
Capacity: 7,6 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Agridiesel MSP 15W-40	**Agridiesel CRD+ 15W-40**	**Dieselfleet CD+ 15W-40**

Change every 400 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Kroontrak MTH 10W-30	**Synfleet SHPD 10W-40**	**Armado Synth 5W-30**

Change every 400 hours

USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Agridiesel MSP 15W-40	**Agridiesel CRD+ 15W-40**	**Dieselfleet CD+ 15W-40**

Change every 50 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Kroontrak MTH 10W-30	**Synfleet SHPD 10W-40**	**Armado Synth 5W-30**

Change every 50 hours

AXLE OSCILLATION REAR

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Q7 MP Calcep Grease WR 2	**Caliplex HD Grease EP 2**	**Q5 MP Calcep Grease EP 2**

DIFFERENTIAL FRONT
Capacity: 8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		

Change every 800 hours

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

MANITOU MANISCOPIC MLT MLT 526 TURBO SERIES 1 PERKINS 1004.4T (1994-1996)

DIFFERENTIAL REAR
Capacity: 8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Agrifluid HT		

Change every 800 hours

HUB REDUCTIONS FRONT
Capacity: 1 liter (each hub)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Change every 800 hours

HUB REDUCTIONS REAR
Capacity: 1 liter (each hub)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Change every 800 hours

TRANSFERBOX
Capacity: 1,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Change every 800 hours

TRANSMISSION
Capacity: 8,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
ATF Almirol		

Change every 800 hours

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

MANITOU MANISCOPIC MLT MLT 526 TURBO SERIES 1 PERKINS 1004.4T (1994-1996)

HYDRAULIC SYSTEM
Capacity: 110 liter (Hydraulic tank)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 46		

Change every 800 hours

HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
LHM +		

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	**Q5 MP Calcep Grease EP 2**	**MP Lithep Grease EP 2**

COOLING SYSTEM
Capacity: 15 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	**Coolant SP 12**	**Coolant -38 Organic NF**

SLIDING PADS JIB

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Q7 MP Calcep Grease WR 2	**Caliplex HD Grease EP 2**	**Q5 MP Calcep Grease EP 2**

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367